

# **PUSIROBOT**


CQPUSI ROBOT CONTROL SYSTEM

## User Manual

---

PMC006B6 Series

Miniature Integrated Stepper Motor Controller



## 1. Version Control

### 1) Update Records

| Date       | Author     | Version | Remark                                                                                                                                                                                                                                                              |
|------------|------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2014-10-19 | huangcheng | V0.1.0  | Initial                                                                                                                                                                                                                                                             |
| 2014-11-25 | Liur       | V0.1.1  | Fix typo                                                                                                                                                                                                                                                            |
| 2014-12-08 | huangcheng | V0.1.2  | Add system control objects; add BOOT and RESET signal descriptions to signal interface J1; merge the external emergency stop enable and external emergency stop trigger mode objects into one object; modify tool screenshots and add related feature descriptions; |
| 2015-5-6   | huangcheng | V0.1.3  | PDO function supplement                                                                                                                                                                                                                                             |
| 2016-6-15  | wentao     | V0.1.4  | Add senseless stall detection                                                                                                                                                                                                                                       |
| 2016-9-22  | Liur       | V0.1.5  | Add function description for close loop                                                                                                                                                                                                                             |
| 2016-11-7  | huangcheng | V0.1.6  | Add external stop3                                                                                                                                                                                                                                                  |
| 2016-11-25 | wentao     | V0.1.7  | Close loop function supplement                                                                                                                                                                                                                                      |
| 2017-10-8  | liur       | V0.1.8  | Add pvtb mode, update feature & function                                                                                                                                                                                                                            |
| 2018-6-15  | jiawei     | V0.1.9  | Migrated from pmc007cxsx                                                                                                                                                                                                                                            |
| 2018-7-23  | hc         | V0.2.0  | Modify instruction                                                                                                                                                                                                                                                  |
| 2018-09-27 | hc         | V0.2.1  | Add analog input function<br>Add step notify related objects                                                                                                                                                                                                        |
| 2018-11-30 | Tanlu      | V0.2.2  | Supplement description for Ext port                                                                                                                                                                                                                                 |
| 2018-12-3  | huangcheng | V0.2.3  | Add sensor type parameter description                                                                                                                                                                                                                               |
| 2019-02-25 | huangcheng | V0.2.4  | Functional description of adding PV/PP mode<br>Adding analog location function description                                                                                                                                                                          |
| 2019-05-12 | liur       | V0.2.5  | 1. Add absolute encoder support;<br>2. Add sensorless stall detection;<br>3. Add smooth mode;<br>4. Extend to 48V supply range.                                                                                                                                     |
| 2019-8-9   | huangcheng | V0.2.6  | Add driver mode settings<br>Add power down behavior settings                                                                                                                                                                                                        |
| 2020-3-10  | chenya     | V0.1.2  | Migrate from PMC007Cx                                                                                                                                                                                                                                               |
| 2021-10-9  | yj         | V0.1.4  | Update some details about commands                                                                                                                                                                                                                                  |
| 2022-3-3   | Wangw      | V0.1.5  | Modify register description                                                                                                                                                                                                                                         |
| 2023-5-5   | Tony       | V0.1.6  | Remove step notify register                                                                                                                                                                                                                                         |
| 2023-3-13  | Tony       | V0.1.7  | 1.Added soft limit control Settings<br>2. Update some details about commands                                                                                                                                                                                        |

| Date       | Author | Version | Remark                                          |
|------------|--------|---------|-------------------------------------------------|
| 2024/7/5   | Liu    | V1.0.0  | Migrated from pmc007bx                          |
| 2024/12/30 | Liu    | V1.0.1  | Modify the output current of the EXT power port |
| 2025/3/11  | Liu    | V1.0.2  | Add a unit description for the high-speed mode  |

## Catalog

|                                                      |    |
|------------------------------------------------------|----|
| 1 Introduction .....                                 | 8  |
| 1.1 Statement of intellectual property right .....   | 8  |
| 1.2 Disclaimer .....                                 | 8  |
| 2 Overview .....                                     | 9  |
| 2.1 General Description .....                        | 9  |
| 2.2 Features .....                                   | 9  |
| 2.3 Production & Ordering Information .....          | 10 |
| 3 Connector Description .....                        | 11 |
| 3.1 Motor connection J7 .....                        | 11 |
| 3.2 Power connection J1 .....                        | 11 |
| 3.3 Solenoid valve connection J2 .....               | 12 |
| 3.4 J3-communication port 1 .....                    | 12 |
| 3.5 J4-communication port 2 .....                    | 12 |
| 3.6 J5-limit connection 1 .....                      | 13 |
| 3.7 J6-limit connection 2 .....                      | 13 |
| 3.8 J9-encoder connection .....                      | 13 |
| 3.9 Modbus network connection .....                  | 13 |
| 3.10 Limit switch connection .....                   | 14 |
| 3.11 Mechanical switch connection .....              | 16 |
| 3.12 Analog Adjusting Speed /Position .....          | 16 |
| 3.13 Solenoid valve/brake connection .....           | 16 |
| 4 Drive mode .....                                   | 17 |
| 4.1 Normal open-loop/closed-loop mode .....          | 17 |
| 4.2 High-speed torque mode .....                     | 17 |
| 5 MODBUS communication .....                         | 18 |
| 5.1 MODBUS introduction .....                        | 18 |
| 5.2 MODBUS frame structure .....                     | 18 |
| 5.3 MODBUS communication configuration .....         | 19 |
| 5.3.1 Node ID .....                                  | 19 |
| 5.3.2 Baud rate .....                                | 19 |
| 5.3.3 Group ID .....                                 | 19 |
| 5.4 System information acquisition .....             | 19 |
| 5.4.1 Device node name .....                         | 19 |
| 5.4.2 Hardware version .....                         | 20 |
| 5.4.3 Software version .....                         | 20 |
| 5.4.4 System control .....                           | 20 |
| 5.5 Motor control parameters .....                   | 20 |
| 5.5.1 Error status .....                             | 20 |
| 5.5.2 Controller status .....                        | 21 |
| 5.6 Basic Instructions .....                         | 21 |
| 5.6.1 Stop stepping command .....                    | 21 |
| 5.6.2 Micro stepping .....                           | 22 |
| 5.6.3 Maximum phase current(Operating current) ..... | 22 |

|                                                                  |    |
|------------------------------------------------------------------|----|
| 5.6.4 Motor position .....                                       | 22 |
| 5.6.5 Encoder position (absolute value encoder closed loop)..... | 23 |
| 5.6.6 Current reduction .....                                    | 23 |
| 5.6.7 Motor enable .....                                         | 24 |
| 5.6.8 Operation mode .....                                       | 24 |
| 5.6.9 Real-time speed(Closed-loop) .....                         | 25 |
| 5.6.10 Stall set(open loop) .....                                | 26 |
| 5.6.11 Stall parameter(open loop) .....                          | 26 |
| 5.7 Position mode .....                                          | 26 |
| 5.7.1 Position mode rotating direction .....                     | 26 |
| 5.7.2 Position mode operating speed .....                        | 26 |
| 5.7.3 Position mode start speed .....                            | 27 |
| 5.7.4 Position mode stop speed .....                             | 27 |
| 5.7.5 Position mode acceleration coefficient .....               | 27 |
| 5.7.6 Position mode deceleration coefficient .....               | 28 |
| 5.7.7 Position mode relative displacement command .....          | 29 |
| 5.7.8 Position mode absolute displacement command .....          | 29 |
| 5.8 External emergency stop .....                                | 29 |
| 5.8.1 External emergency stop enable .....                       | 30 |
| 5.8.2 The trigger mode of external emergency stop .....          | 30 |
| 5.8.3 Sensor type .....                                          | 30 |
| 5.8.4 Debouncing delay .....                                     | 31 |
| 5.9 General IO port .....                                        | 31 |
| 5.9.1 IO port direction .....                                    | 31 |
| 5.9.2 General IO port value .....                                | 33 |
| 5.10 Closed-loop control .....                                   | 33 |
| 5.10.1 Encoder resolution .....                                  | 33 |
| 5.10.2 KP parameter .....                                        | 34 |
| 5.10.3 KI parameter .....                                        | 34 |
| 5.10.4 KD parameter .....                                        | 34 |
| 5.10.5 Pre-filtering parameter .....                             | 34 |
| 5.10.6 Post-filtering parameter .....                            | 34 |
| 5.10.7 Stall length parameter .....                              | 35 |
| 5.10.8 Torque ring enable(High-speed torque mode switch) .....   | 35 |
| 5.10.9 Autosave when power is off enable .....                   | 35 |
| 5.11 PP motion mode .....                                        | 35 |
| 5.11.1 PP mode Acceleration .....                                | 36 |
| 5.11.2 PP mode Deceleration .....                                | 36 |
| 5.11.3 PP mode Start speed .....                                 | 36 |
| 5.11.4 PP mode Stop speed .....                                  | 37 |
| 5.11.5 PP mode Control word .....                                | 37 |
| 5.11.6 PP Status word .....                                      | 37 |
| 5.11.7 PP mode Running Speed .....                               | 38 |
| 5.11.8 PP mode Target Location .....                             | 38 |

|                                                                                                                                                                      |    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| 5.11.9 PP mode work timing .....                                                                                                                                     | 38 |
| 5.12 PV Mode .....                                                                                                                                                   | 41 |
| 5.13 Analog positioning .....                                                                                                                                        | 41 |
| 5.13.1 Enable analog positioning .....                                                                                                                               | 42 |
| 5.13.2 Analog initial AD code .....                                                                                                                                  | 42 |
| 5.13.3 Analog adjustment interval .....                                                                                                                              | 42 |
| 5.13.4 Analog regulating trigger value .....                                                                                                                         | 42 |
| 5.13.5 Minimum value of analog position .....                                                                                                                        | 43 |
| 5.13.6 Maximum value of analog position .....                                                                                                                        | 43 |
| 5.13.7 Analogue input read .....                                                                                                                                     | 43 |
| 5.14 Synchronous position Motion mode .....                                                                                                                          | 43 |
| 5.14.1 SP speed .....                                                                                                                                                | 44 |
| 5.14.2 SP position .....                                                                                                                                             | 44 |
| 5.14.3 SP commands .....                                                                                                                                             | 44 |
| 5.15 Soft limit function .....                                                                                                                                       | 45 |
| 5.15.1 Soft limit enable .....                                                                                                                                       | 45 |
| 5.15.2 Upper limit position .....                                                                                                                                    | 45 |
| 5.15.3 Lower limit position .....                                                                                                                                    | 45 |
| 5.16 Brake control .....                                                                                                                                             | 46 |
| The PMC006B3 supports brake control, and the output duty cycle can be adjusted via software to prevent the brake from overheating when powered for a long time. .... | 46 |
| 5.17 Power loss behavior .....                                                                                                                                       | 46 |
| 5.17.1 Power-down behavior control word .....                                                                                                                        | 46 |
| 5.17.2 Power-down off-line voltage .....                                                                                                                             | 46 |
| 5.17.3 Power-off brake threshold voltage .....                                                                                                                       | 46 |
| 5.17.4 Supply voltage reading .....                                                                                                                                  | 47 |
| 5.18 Open and closed loop function switching .....                                                                                                                   | 47 |
| 5.19 Temperature threshold .....                                                                                                                                     | 47 |
| 5.20 Motor wiring configuration .....                                                                                                                                | 47 |
| 5.21 Homing configuration .....                                                                                                                                      | 48 |
| 5.21.1 Homing speed .....                                                                                                                                            | 48 |
| 5.21.2 Homing distance .....                                                                                                                                         | 48 |
| 5.22 offline programming .....                                                                                                                                       | 48 |
| 5.22.1 The total number of offline program instructions .....                                                                                                        | 49 |
| 5.22.2 Offline automatic operation enable .....                                                                                                                      | 49 |
| 5.22.3 Offline program pointers .....                                                                                                                                | 49 |
| 5.22.4 Set the content of the offline command .....                                                                                                                  | 49 |
| 5.22.5 Save offline commands .....                                                                                                                                   | 49 |
| 5.22.6 Test run instructions .....                                                                                                                                   | 50 |
| 6 Electrical Characteristics .....                                                                                                                                   | 50 |
| 7 Dimensions (unit: mm) .....                                                                                                                                        | 51 |
| 8 Appendix 1 instruction table .....                                                                                                                                 | 52 |
| Analog initial AD code .....                                                                                                                                         | 54 |
| 9 Appendix 2 Communications Example .....                                                                                                                            | 54 |

|                                                           |    |
|-----------------------------------------------------------|----|
| 9.1 Modbus/RTU supported function codes .....             | 54 |
| 9.2 Master Station communication parameter setting: ..... | 54 |
| 9.3 Modbus master station message write operation .....   | 55 |
| 9.4 Modbus/RTU control examples .....                     | 55 |
| 9.4.1 Relative position control .....                     | 55 |
| 9.4.2 Absolute position control .....                     | 56 |
| 9.4.3 Speed mode control .....                            | 56 |
| 9.4.4 Commonly used fixed parameter settings .....        | 57 |
| 10 Appendix 3 CRC code .....                              | 57 |
| 11 Appendix 3 Modbus/RTU 16bits CRC check example .....   | 58 |
| 12 Appendix 2 Error code table .....                      | 61 |

## **1 Introduction**

### **1.1 Statement of intellectual property right**

PMC006B6 series controller has been applied for the following national patent:

- Controller scheme and method have been applied for the protection of the invention patent.
- Controller circuit has been applied for the protection of utility mode patent.
- Controller appearance has been applied for the protection of appearance patent

protection.

PMC006B6 series controller has embedded firmware code, it would be considered as a violation of intellectual property protection act and regulations that any behavior of trying to destroy the function of firmware code protection. If this behavior acquires the software or other achievements of intellectual property protection without authorization of CQPUSI, CQPUSI has the right to stop such behavior by filing a lawsuit according to the act.

### **1.2 Disclaimer**

The using method of the device and other content in the description of this manual is only used to provide convenience for you, and may be update in future version. To ensure the application conforms to the technical specifications is the responsibility of your own. CQPUSI does not make any form of statement

or guarantee to the information, which include but not limited to usage, quality, performance, merchantability or applicability of specific purpose. CQPUSI is not responsible for these information and the consequences result caused by such information. If the CQPUSI device is used for life support and/or life safety applications, all risks are borne by the buyer. The buyer agrees to protect the CQPUSI from legal liability and compensation for any injury, claim, lawsuit or loss caused by the application.

## 2 Overview

### 2.1 General Description


PMC006B6 is a kind of miniature integrated stepper motor microstepping controller, which can be directly installed in the rear of NEMA23/34 series stepper motor. The PMC006 series controllers are available in a variety of modes based on MODBUS RTU bus control and different current levels. With the PMC006B6 stepper motor controller, it is easy to implement an industrial control network system with up to 32 nodes, and encoder-based closed-loop control can be realized according to user requirements. It is suitable for a wide range of high-precision and wide-range industrial applications.

### 2.2 Features

- ✓ Wide range of 9-48V single voltage supply
- ✓ Output current 0.2A ~ 6A. Adjustable phase current by commands
- ✓ Automatic control of S curve acceleration and deceleration
- ✓ Support Position/Velocity/PP/PV/SP/Analog Position/Analog velocity mode etc. motion mode
- ✓ Support 200-8000PPR incremental encoder; Supports single-turn and multi-turn absolute encoders;
- ✓ Support automatic deviation correction;
- ✓ Support normal open-loop mode, normal closed-loop mode, closed-loop high-speed torque mode
- ✓ Electromagnetic brake control function
- ✓ Sensor-less stall detection
- ✓ Power-down detection
- ✓ Support 0/2/4/8/16/32/64/128 microstepping resolution
- ✓ Suitable for 4/6/8 lines of 2 phase stepper motor
- ✓ Automatic over-temperature, over-current, under-voltage and over-voltage protection
- ✓ Analog Input Application (Special edition)
- ✓ Hot-plug protection, power misconnection protection
- ✓ Miniature size 56.2mmx56.2mmx32.1mm

## 2.3 Production & Ordering Information


In order to serve you quicker and better, please provide the product number in following format when ordering PMC006B6:



Remark:

E: Closed-loop type.

### 3 Connector Description



#### 3.1 Motor connection J7

| Pin no     | 1   | 2   | 3   | 4   |
|------------|-----|-----|-----|-----|
| Designator | M10 | M11 | M20 | M21 |

Description:

M10: Motor A+ phase

M11: Motor A- phase

M20: Motor B+ phase

M21: Motor B- phase

**WARNING:** The wrong phase wire of the power supply or motor can permanently damage the controller ( For closed-loop, correspond to the red, blue, black, and green wiring)

#### 3.2 Power connection J1

| Pin no:    | 1   | 2   |
|------------|-----|-----|
| Designator | GND | VCC |

Description:

VCC: Supply voltage, 9-48V.

GND: Supply voltage ground.

### 3.3 Solenoid valve connection J2

|            |       |       |      |
|------------|-------|-------|------|
| Pin no:    | 1     | 2     | 3    |
| Designator | Coil- | Coil+ | FSET |

Description:

Coil+: Solenoid valve/brake positive control terminal, its voltage is equal to the voltage of power supply

Coil-: Solenoid valve/brake negative control terminal;

NC: Reserved port, no function

Warning: The Coil+ pin is the same as the supply voltage, be careful not to short with DVDD, GND, or other signal lines

### 3.4 J3-communication port 1

|            |     |      |      |
|------------|-----|------|------|
| Pin no:    | 1   | 2    | 3    |
| Designator | GND | 485B | 485A |

Description:

485A: Connect the transceiver interface of the 485 module

485B: Connect the transceiver interface of the 485 module

GND: Controller digital ground

A single unit only connected to one communication port, when networking, directly plug in the access bus by using communication port

### 3.5 J4-communication port 2

|            |     |      |      |
|------------|-----|------|------|
| Pin no:    | 1   | 2    | 3    |
| Designator | GND | 485B | 485A |

Description:

485A: Connect the transceiver interface of the 485 module

485B: Connect the transceiver interface of the 485 module

GND: Controller digital ground

### 3.6 J5-limit connection 1

|            |      |     |       |       |
|------------|------|-----|-------|-------|
| Pin no:    | 1    | 2   | 3     | 4     |
| Designator | DVDD | GND | EXT1- | EXT1+ |

Description:

DVDD: Controller voltage output(+5V). Maximum current is 250mA.

GND: Controller digital ground.

EXT1+: External limit switch signal input 1 positive, 3~5.5V.

EXT1-: External limit switch signal input 1 negative

### 3.7 J6-limit connection 2

|            |         |     |       |          |
|------------|---------|-----|-------|----------|
| Pin no:    | 1       | 2   | 3     | 4        |
| Designator | OUT-VDD | GND | EXT2- | EXT2+/AN |

Description:

OUT-VDD: GPIO8 controlled 5V output, 50mA max

GND: Controller digital ground.

EXT2-: External limit switch signal input 2 negative

EXT2+: External limit switch signal input 2 positive, 3~5.5V.

AN: Can be used as an analog input interface in the special version, input voltage 0-3.3V.

Can be 0-24V (or 10mA) input in the special version.

Note: The analog input and the second limit port can only be realized by selecting one of the two functions.

### 3.8 J9-encoder connection

|            |      |     |   |   |   |   |
|------------|------|-----|---|---|---|---|
| Pin no:    | 1    | 2   | 3 | 4 | 5 | 6 |
| Designator | DVDD | GND | A | B | Z | - |

Description:

DVDD: Controller voltage output(+5V). Maximum current is 100mA.

GND: Controller digital ground.

A: Encoder phase A signal

B: Encoder phase B signal


Z: Encoder phase Z signal

### 3.9 Modbus network connection

Modbus/RTU has a common physical layer with standard RS-232 or RS-485, and can be configured with 1~32 slave addresses; RS-485 networks are built topology, usually with a 120 ohm termination resistor connected in parallel at the end of the slave device. Modbus/RTU supports half-duplex wiring, and we generally recommend half-duplex wiring to build RTU


communication networks.

Note: It is recommended to use a 120 ohm shielded twisted pair dedicated to the MODBUS bus and a 120 ohm termination resistor at each end of the twisted pair. The PTA2C in the diagram is a third-party USB-RS485 converter.



### 3.10 Limit switch connection

The PMC006B6 controller has two special pins EXT1/EXT2 for connecting external limit switches, the trigger mode of each pin can be selected in real time through the command, the factory default value is valid for the falling edge trigger, at this time, the corresponding EXT1/EXT2 is from high level to low level jump, there is optodephone isolation inside the controller, when the optocoupler input positive and input negative correctly form a loop, and are in the normal conduction state, then EXT1/EXT2 will change from high level to low level, Figure below.




There are two types of common external limit switches, one is a four-wire through-beam optocoupler without an internal circuit, and the other is a three-wire or five-wire optocoupler with an internal circuit, which is divided into PNP type and NPN type. And there is a difference between light conduction and shading conduction. For different types of optocouplers, you can refer to the following wiring methods:

#### ✧ NPN type three-wire optocoupler


When the light is in, it is turned on and the occlusion is triggered, and the rising edge

trigger mode is configured, as shown in Figure below. Note that in this case, EXT1/EXT2 both need the OUT-VDD pin of J6 as the power supply. If the DVDD pin of J5 is used, an external current-limiting resistor is required to avoid burning the light-emitting diode of the optocoupler.




✧ NPN type three-wire optocoupler

When entering the light, it is turned on and the occlusion is triggered, and it is configured as the rising edge trigger mode




✧ PNP type three-wire optocoupler

When entering the light, it is turned on and the occlusion is triggered, and it is configured as the rising edge trigger mode



### 3.11 Mechanical switch connection

When using mechanical button switch or relay contact as a limit, it should be directly connected, EXT access DVDD, EXT- access GND, usually not conduction, press on, configure as the descending edge trigger mode. As shown in the figure below.



### 3.12 Analog Adjusting Speed /Position

In the special version, the PMC006B6 controller can use the analog speed regulation function and the analog positioning function in offline operation mode. In this case, the AN pin is used as an analog input port, so please contact sales in advance if you need to purchase it.


In offline mode, the AN pin is used as an analog input port in this application, which can be directly connected to an external input voltage in the range of 0~3.3V. When using PLC or other industrial control equipment to output 4~20mA or 0-24V analog control, special instructions are required to distinguish the version.

Analog speed regulation: Set a speed range, the minimum value corresponds to the input minimum value, and the maximum speed value corresponds to the input maximum value. By adjusting the input value, the motor rotates at the corresponding speed.

Analog positioning: Set a position range, the minimum value of the position corresponds to the minimum value of the input, and the maximum value of the position corresponds to the maximum value of the input. The current position of the motor is adjusted to change the input value so that the motor stops at the specified position. Values such as speed are fixed when set.

### 3.13 Solenoid valve/brake connection

The PMC006B6 controller supports direct control of inductive loads such as solenoid valves, solenoids, solenoid brakes, and DC motors. As shown in the figure below, the load can be connected to the Coil and Coil- pins on the controller J1. The output voltage is the same as the input power supply voltage of the controller, and the output current is up to 800mA, in order to reduce the working temperature of the load coil, the controller supports PWM dynamic voltage adjustment function, and the user can modify the output voltage in real time through instructions.



## 4 Drive mode

### 4.1 Normal open-loop/closed-loop mode

The applicable speed range of normal mode is 10-1200RPM, and the unit of operating parameters such as speed and start-stop speed is PPS. Open-loop and closed-loop switching can be made by modifying register 0x6036-6037.

### 4.2 High-speed torque mode

The high-speed torque mode is suitable for the speed range of 1000-1200RPM, and the controller can be switched from normal mode to high-speed torque mode by enabling the torque loop (0x605d). The high-speed torque function is as follows:

1. In torque mode, the motor will automatically match the magnetism when powered on to ensure accurate position;
2. The controller microstepping is fixed and cannot be manually modified;
3. The automatic deviation correction function is started when the pre-filter > 20;
4. If disabled, the PID parameter does not take effect. After enabled, the default parameters KP 15, KI 8, and KD 25 are modified according to the operation requirements (it is not recommended to modify them unless there are special requirements), the value is written to the register, and the power-off save instruction is written once before it takes effect. The closed-loop version works.
5. The torque mode will automatically slow down when encountering resistance, and will automatically increase speed when the resistance decreases; The torque is maintained at a constant maximum value during automatic deviation correction, and the deviation correction speed is 400RPM;
6. Units of High Speed Torque Mode:
  - a. Start speed, stop speed, maximum speed: 0.1lines/ms, for example, set 8000, that is, 800000lines/s, 4000ppr encoder is 3000rpm; Default parameters: startup speed 20 x 0.1lines/ms, stop speed 20 x 0.1lines/ms


b. Acceleration and deceleration: 0.01 lines/ms<sup>2</sup>, for example, 5 represents 50000 lines/s<sup>2</sup>, default parameters: acceleration 32 \* 0.01 lines/ms<sup>2</sup>, deceleration 32 \* 0.01 lines/ms<sup>2</sup>

## 5 MODBUS communication

### 5.1 MODBUS introduction


Modbus protocol, which is a bus protocol that allows the master station and one or more slave stations to share data, consists of 16-bit registers. The master can read and write individual or multiple registers.

the standard Modbus port on the controller is using a RS-232 compatible serial interface that defines connectors, wiring cables, signal levels, transmission baud rates, and parity. Controller communication uses master-slave technology, that is, the host can start data transmission, called query. Other devices (slave) return the response to the query or process the actions required by the query. Host equipment shall include master processors, programmers and PLC. The slave includes a programmable controller, a servo drive and a step drive. MODBUS RTU network structure is shown below :



### 5.2 MODBUS frame structure

Modbus/RTU is a master-slave technique, and the CRC verification range is from the device address bit to the data bit; the detailed message format of each function code, please see appendix. Modbus/RTU message frames are as follows :



as a master-slave communication technology, data can be transmitted between a master station (e.g.: PC) and 32 substations (e.g.: PMC007Bx). The following protocols must be observed

between master and slave stations:

- 1) All information transmitted on the RS485 communication loop will be initialized and controlled by the master station;
- 2) No communication can begin at a sub-station;
- 3) All communications in the RS485 loop are transmitted in frame format;
- 4) If the master or sub-station receives a frame format containing unknown commands, it does not respond;

### 5.3 MODBUS communication configuration

PMC006 is set to 1 node ID and baud rate of 9600 by default, and users can modify the settings through the supporting MODBUS master debugging tool.

#### 5.3.1 Node ID

|                  |         |
|------------------|---------|
| Object name      | Node ID |
| Instruct address | 0x2028  |
| Object type      | U8,rw   |
| Range            | 1-127   |
| Storage type     | ROM     |
| Default value    | 1       |

#### 5.3.2 Baud rate

|                  |                                    |
|------------------|------------------------------------|
| Object name      | Baud rate                          |
| Instruct address | 0x202a..0x202b                     |
| Object type      | U8,rw                              |
| Range            | 4800/9600/19200/38400/51200/115200 |
| Storage type     | ROM                                |
| Default value    | 9600                               |

#### 5.3.3 Group ID

|                  |          |
|------------------|----------|
| Object name      | Group ID |
| Instruct address | 0x200e   |
| Object type      | U8,rw    |
| Range            | 1-127    |
| Storage type     | RAM      |
| Default value    | 1        |

In a MODBUS RTU network, the function remains.

### 5.4 System information acquisition

#### 5.4.1 Device node name

|             |                  |
|-------------|------------------|
| Object name | Device node name |
|-------------|------------------|

|                  |            |
|------------------|------------|
| Instruct address | 0x101a..21 |
| Object type      | string,ro  |
| Range            | -          |
| Storage type     | ROM        |
| Default value    | -          |

#### 5.4.2 Hardware version

|                  |                  |
|------------------|------------------|
| Object name      | Hardware version |
| Instruct address | 0x1022..23       |
| Object type      | string,ro        |
| Range            | -                |
| Storage type     | ROM              |
| Default value    | -                |

#### 5.4.3 Software version

|                  |                  |
|------------------|------------------|
| Object name      | Software version |
| Instruct address | 0x1024..25       |
| Object type      | string,ro        |
| Range            | -                |
| Storage type     | ROM              |
| Default value    | -                |

#### 5.4.4 System control

|                  |                |
|------------------|----------------|
| Object name      | System control |
| Instruct address | 0x200f         |
| Object type      | U8,ro          |
| Range            | 1, 2, 3        |
| Storage type     | RAM            |
| Default value    | -              |

System control values are defined as follows:

- 1: Jump to bootloader
- 2: Save Object Dictionary parameters
- 3: Reset factory settings

Note: The parameters stored in the object dictionary with the storage type ROM are temporarily stored in memory after being written by the command, if you need to save them permanently, you need to save the object dictionary parameters by powering off. This operation cannot be written to the process to prevent fast erase and write the ROM to accelerate the consumption of service life.

### 5.5 Motor control parameters

#### 5.5.1 Error status

|             |              |
|-------------|--------------|
| Object name | Error status |
|-------------|--------------|

|                  |        |
|------------------|--------|
| Instruct address | 0x6000 |
| Object type      | U8,rw  |
| Range            | bit    |
| Storage type     | RAM    |
| Default value    | 0      |

Driver state are defined as follows:

Bit0: OTS, over temperature shutdown

Bit1: AOCP, motor over-current

Bit2: BOCP, magnetic core position error

Bit3: APDF, Wrong direction of rotation when facing magnetism

Bit4: BPDF, Wrong rotation angle when facing magnetism

Bit5: UVLO, low supply voltage warning

Bit6: CERR, the rotation direction is wrong when magnetizing

Bit7: DERR, the rotation angle is wrong when magnetizing

Clear the corresponding error state by writing 1 to the corresponding bit, for example, write 0x18 to clear the flags of bit3 and bit4, that is, to clear the wrong rotation direction when facing the magnet and the wrong rotation angle when facing the magnet, and write FF to be fully clear.

Note: bit2/bit3/bit4/bit6/bit7 only takes effect for high-speed torque mode.

### 5.5.2 Controller status

|                  |                   |
|------------------|-------------------|
| Object name      | Controller status |
| Instruct address | 0x6001            |
| Object type      | U8,rw             |
| Range            | bit               |
| Storage type     | RAM               |
| Default value    | 0                 |

Controller status is defined as follows:

Bit0: External stop 1

Bit1: External stop 2

Bit2: Stall state

Bit3: busy state

Bit4: External stop 3

Bit8: Resets the status bit

In addition to the busy state, you can write 1 to clear the response state, and the usage is the same as 6000h.

## 5.6 Basic Instructions

### 5.6.1 Stop stepping command

|                  |                       |
|------------------|-----------------------|
| Object name      | Stop stepping command |
| Instruct address | 0x6053                |

|               |       |
|---------------|-------|
| Object type   | U8,rw |
| Range         | 0     |
| Storage type  | RAM   |
| Default value | 0     |

The instruction immediately terminates the motor operation without a deceleration process.

### 5.6.2 Micro stepping

|                  |                      |
|------------------|----------------------|
| Object name      | Micro stepping       |
| Instruct address | 0x600c               |
| Object type      | U16,rw               |
| Range            | 0,2,4,8,16,32,64,128 |
| Storage type     | ROM                  |
| Default value    | 0                    |

The motor is  $360^{\circ}$  per revolution, and the step angle of a conventional 2-phase stepper motor is  $1.8^{\circ}$ , i.e. 200 pulses per revolution are required at 0 microstepping. In the same way, 400 pulses per revolution are required under 2 microstepping, and 1600 pulses per revolution are required under 8 microstepping.

In high-speed torque mode, the microstepping can only be read and cannot be set.

### 5.6.3 Maximum phase current(Operating current)

|                  |                                          |
|------------------|------------------------------------------|
| Object name      | Maximum phase current(Operating current) |
| Instruct address | 0x600d                                   |
| Object type      | U16,rw                                   |
| Range            | 0-2000                                   |
| Storage type     | ROM                                      |
| Default value    | 658                                      |

The maximum phase current is the supply current to the motor when it is working normally, and is generally set to the rated current of the motor. In some cases, it can be adjusted appropriately, generally with a range of  $\pm 20\%$  and not more than 50%. Excessive current will cause the motor to heat up seriously, and long-term operation of the motor may have the risk of demagnetization, affecting the service life of the motor.

### 5.6.4 Motor position

|                  |                           |
|------------------|---------------------------|
| Object name      | Motor position            |
| Instruct address | 0x600e..f                 |
| Object type      | S32,rw                    |
| Range            | $-2^{31} \sim (2^{31}-1)$ |
| Storage type     | RAM                       |
| Default value    | 0                         |

The current motor position is represented by the conversion of the number of pulses per revolution. The incremental type is a quadruple of the PPR, for example, 4000 lines are 16000

pulses for one revolution of the motor. The absolute accuracy is  $2^{14}$ , 16384 pulses per revolution.

In open-loop mode, the motor position is not saved, and the position information is automatically cleared to zero after the controller is powered off.

In incremental closed-loop mode, motor positions are not saved for conventional applications. There is a switch inside the controller that can record the position of the motor before the power is off. It is generally used in conjunction with the brake to prevent the motor from moving in the event of a power failure. Otherwise, the saved location is not referential.

In the closed-loop mode of absolute single-turn value, the controller can record the change of motor position within one turn, and the value of the extra turn will be automatically discarded after the power failure. Values greater than one turn are saved, and you can refer to the same application method as the incremental type.

Multi-turn absolute closed-loop mode, which can record the change of motor position in real time, and can still work after power failure. The position of the limit switch can be omitted.

#### 5.6.5 Encoder position (absolute value encoder closed loop)

|                  |                           |
|------------------|---------------------------|
| Object Name      | Encoder position          |
| Instruct address | 0x6089..8a                |
| Instruct address | S32,rw                    |
| Object type      | $-2^{31} \sim (2^{31}-1)$ |
| Range            | RAM                       |
| Storage type     | 0                         |

For now only single-turn and multi-turn value reading is open, and the encoder feedback position is read in real time, and the value cannot be changed by command.

#### 5.6.6 Current reduction

|                  |                               |
|------------------|-------------------------------|
| Object name      | Current reduction coefficient |
| Instruct address | 0x6010                        |
| Object type      | U8,rw                         |
| Range            | 0-3                           |
| Storage type     | ROM                           |
| Default value    | 2                             |

The value is defined as follows:

- 0: Decay 0%;
- 1: Decay 50%
- 2: Decay 75%
- 3: Decay 87.5%

0-3 corresponds to 4 gears of 100%, 50%, 25% and 12.5% idle current supply, the ratio is based on the percentage of the maximum phase current of 600Dh. The default is 50% for 2nd gear, and when the motor is idle, it will switch to idle current power supply.

**5.6.7 Motor enable**

|                  |              |
|------------------|--------------|
| Object name      | Motor enable |
| Instruct address | 0x6011       |
| Object type      | U8,rw        |
| Range            | 0,1          |
| Storage type     | RAM          |
| Default value    | 1            |

The value of the motor is defined as follows:

0: Offline

1: Motor enable

Release control of the motor immediately after setting offline, the motor loses power supply and loses holding torque.

The controller is enabled by default, and no settings need to be manually written for power-on.

**5.6.8 Operation mode**

|                  |                |
|------------------|----------------|
| Object name      | Operation mode |
| Instruct address | 0x6007         |
| Object type      | U8,rw          |
| Range            | 0,1, 4, 5      |
| Storage type     | RAM            |
| Default value    | 0              |

The value of the motor operation mode is defined as follows:

0: Position mode

1: Speed mode(including analog speed regulation)

4: PP (Profile Position) mode (including analog positioning)

5: PV(Profile Velocity) mode

Location Mode:

The setting of the position mode is simple, easy to operate, you can use the relative or absolute running motion mode, after setting the running speed and direction of movement, give the corresponding running instructions, the motor will move to the corresponding position, because the acceleration and deceleration is the gear setting, the acceleration and deceleration can not be accurately adjusted, the equipment or parameters need to be debugged according to the load situation, the stepping command setting needs to be sent when the controller is idle, so to change the speed, change the stepping position, you need to wait for the motor to stop and then send the corresponding instructions, before it can run, Otherwise, the command will not be received.

Speed Mode:

After entering the speed mode, set the running speed and the motor will rotate all the time. Unless the limit or stop stepping command is triggered or the speed mode is exited, the motor will rotate according to the running speed, and the running speed can be changed (positive positive rotation, negative negative reversal) and speed adjustment can be adjusted by setting

the running speed during operation, without stopping the movement. The speed mode and the position mode share the same parameter register, and the acceleration and deceleration and start-stop speed cannot be modified during operation. The speed mode is easy to set and stable, which is convenient for long-distance variable speed movement. If it is at high speed, changing direction directly may cause stalling. The speed setting needs to be adjusted according to the actual operation.

#### PP Mode:

PP mode uses trapezoidal acceleration and deceleration movement, each run can change the acceleration and deceleration, start and stop speed, running speed, running direction and target position, through the unified execution of the control word, you can switch the running task or preset the next task during the movement. PP mode can also use absolute or relative operation modes, and the acceleration and deceleration value settings are open to better control the smoothness of the operation and perform more complex operation planning.

#### PV Mode:

PV mode is called Profile Velocity Mode, which also uses trapezoidal acceleration and deceleration mode, and shares parameters such as start-stop speed, acceleration and deceleration, and running speed with PP mode. After entering the PV mode, you need to set the running speed for the first run, use the control word to start the run, and then change the speed only need to modify the value of the running speed.

During PV mode operation, the motor will rotate according to the set running speed, and the stop can be achieved by exiting or switching the mode/setting the running speed to 0/step stop command. During the operation, the running speed can be set to change the running direction (positive positive rotation, negative negative reversal) and adjust the speed magnitude, without pausing the movement to set the parameters. Because the acceleration and deceleration are controllable and the acceleration and deceleration are uniform, it is easier to calculate the running time, and changing the running direction at high speed will not cause stalling.

### 5.6.9 Real-time speed(Closed-loop)

|                  |                                                 |
|------------------|-------------------------------------------------|
| Object name      | Real-time speed(pps)                            |
| Unit             | Normal mode pps<br>High-speed mode 0.1 lines/ms |
| Instruct address | 0x607f/6080                                     |
| Object type      | S32, ro                                         |
| Range            | -300000~+300000                                 |
| Storage type     | RAM                                             |
| Default value    | 0                                               |

For parameters that are only available under the closed-loop function, an error will be reported when the open-loop reading is performed.

Real-time velocity is a signed variable with a direction of 1 when positive and a direction of 0 when negative. At high speed torque, the reading value is 100 times the actual operating speed.

**5.6.10 Stall set(open loop)**

|                  |                                         |
|------------------|-----------------------------------------|
| Object name      | Whether the motor stops after stall set |
| Instruct address | 0x6043                                  |
| Object type      | Record                                  |
| Range            | 0-1                                     |
| Storage type     | ROM                                     |
| Default value    | 0                                       |

When set to 1, the motor will stop after a stall; when set to 0, the motor will not stop. It is unrelated to closed-loop applications.

**5.6.11 Stall parameter(open loop)**

|                  |                               |
|------------------|-------------------------------|
| Object name      | Set stall detection parameter |
| Instruct address | 0x6039                        |
| Object type      | U16, rw                       |
| Range            | bit                           |
| Storage type     | ROM                           |
| Default value    | 0                             |

The definition of each detection parameter bit is as follows:

Bit0~6: Stall threshold, signed number;

Bit7~15: Reserved;

The PMC006BX controller uses the back electromotive force of the two-phase windings to achieve sensorless stall detection. Its accuracy is affected by various factors such as current, microstepping, voltage, and motor parameters, among which motor speed and phase inductance are particularly significant. The stall threshold is usually set in the range of -10 to 10. It is unrelated to closed-loop applications.

**5.7 Position mode****5.7.1 Position mode rotating direction**

|                  |                    |
|------------------|--------------------|
| Object name      | Rotating direction |
| Instruct address | 0x6002             |
| Object type      | U8,rw              |
| Range            | 0,1                |
| Storage type     | RAM                |
| Default value    | 1                  |

The value of the rotation direction is defined as follows:

0: forward

1: backward

**5.7.2 Position mode operating speed**

|             |                                     |
|-------------|-------------------------------------|
| Object name | Location mode operating speed (pps) |
|-------------|-------------------------------------|

|                  |                                                 |
|------------------|-------------------------------------------------|
| Unit             | Normal mode pps<br>High-speed mode 0.1 lines/ms |
| Instruct address | 0x6003..4                                       |
| Object type      | S32,rw                                          |
| Range            | -200000 ~ +200000                               |
| Storage type     | RAM                                             |
| Default value    | 0                                               |

Note: the speed is a signed variable. Positive represents that the direction is 1, and negative represents that the direction is 0. So in the displacement mode it is recommended to set the speed firstly , and then set the direction.

### 5.7.3 Position mode start speed

|                  |                                                 |
|------------------|-------------------------------------------------|
| Object name      | Start speed(Unit: pps)                          |
| Unit             | Normal mode pps<br>High-speed mode 0.1 lines/ms |
| Instruct address | 0x6008                                          |
| Object type      | U16,rw                                          |
| Range            | 0-0xFFFF                                        |
| Storage type     | ROM                                             |
| Default value    | 600                                             |

### 5.7.4 Position mode stop speed

|                  |                                                 |
|------------------|-------------------------------------------------|
| Object name      | Stop speed(Unit: pps)                           |
| Unit             | Normal mode pps<br>High-speed mode 0.1 lines/ms |
| Instruct address | 0x6009                                          |
| Object type      | U16,rw                                          |
| Range            | 0-0xFFFF                                        |
| Storage type     | ROM                                             |
| Default value    | 600                                             |

If the start speed and stop speed jump directly, for example, jump from 0 to the maximum speed of starting speed and then accelerate or decelerate from maximum speed to stop speed and then jump to 0, so the start and stop speed cannot be set to 0.

### 5.7.5 Position mode acceleration coefficient

|                  |                                                                                |
|------------------|--------------------------------------------------------------------------------|
| Object name      | Acceleration coefficient                                                       |
| Unit             | The normal mode has 8 levels.<br>High-speed mode is 0.01 lines/ms <sup>2</sup> |
| Instruct address | 0x600a                                                                         |
| Object type      | U16,rw                                                                         |
| Range            | Normal mode 0-8<br>High-speed mode 0-0xFFFF                                    |

|               |     |
|---------------|-----|
| Storage type  | ROM |
| Default value | 8   |

### 5.7.6 Position mode deceleration coefficient

|                  |                                                                                |
|------------------|--------------------------------------------------------------------------------|
| Object name      | Deceleration coefficient                                                       |
| Unit             | The normal mode has 8 levels.<br>High-speed mode is 0.01 lines/ms <sup>2</sup> |
| Instruct address | 0x600b                                                                         |
| Object type      | U16,rw                                                                         |
| Range            | Normal mode 0-8<br>High-speed mode 0-0xFFFF                                    |
| Storage type     | ROM                                                                            |
| Default value    | 8                                                                              |




Figure 5- 1

The PMC006B6 controller uses S curve acceleration and deceleration. As shown in Figure 5-1, the start-up speed, stop speed, acceleration and deceleration can be configured separately, and the acceleration and deceleration support 1~8 for a total of 8 gears, and the corresponding acceleration values for each gear are as follows. PMC006B6 The acceleration value of the 1st gear is the largest, and the acceleration value of the 8th gear is the smallest.

| Gear | Acceleration and deceleration value (PPS2)     |
|------|------------------------------------------------|
| 0    | Acceleration and deceleration cannot be enable |
| 1    | 77440                                          |
| 2    | 48410                                          |
| 3    | 27170                                          |
| 4    | 21510                                          |
| 5    | 14080                                          |
| 6    | 10460                                          |
| 7    | 6915                                           |
| 8    | 5210                                           |

### 5.7.7 Position mode relative displacement command

|                  |                               |
|------------------|-------------------------------|
| Object name      | Relative displacement command |
| Instruct address | 0x6005..6                     |
| Object type      | U32,rw                        |
| Range            | 0x0-0xFFFFFFFF                |
| Storage type     | RAM                           |
| Default value    | 0                             |

Relative to the current motor position, let the motor run for a set number of steps, and an error will be reported if the displacement is 0. Write step number, then the controller will control the motor rotate a given number of steps which is calculated based on the current microstepping settings at the setting direction, speed and acceleration.

In open-loop mode, the number of steps is calculated based on the current microstepping setting.

In the incremental encoder closed-loop mode, the input unit is 4 times the resolution of the encoder, for example, CPR=4000, then the motor rotates once when 16000 is input.

In the closed-loop mode of the absolute encoder, the input unit is the same as the encoder counting unit, for example, if the accuracy is 14 bits, then the motor rotates once when 16384 is entered.

### 5.7.8 Position mode absolute displacement command

|                  |                               |
|------------------|-------------------------------|
| Object name      | Absolute displacement command |
| Instruct address | 0x6044..45                    |
| Object name      | S32,rw                        |
| Range            | $-2^{31} \sim (2^{31}-1)$     |
| Storage type     | RAM                           |
| Default value    | 0                             |

Run directly to the specified position, and an error will be reported if the displacement is 0. The absolute displacement command gives the target position, and the controller will automatically calculate the direction and the required number of steps, and control the stepper motor to rotate the specified position according to the set speed and acceleration.

Note: The units of the above operating parameters are only for normal mode

## 5.8 External emergency stop

The PMC006B6 controller provides 2 dedicated limit switch input ports(EXT1/EXT2), which can be used as an emergency stop or zero search function.

When the emergency stop function is enabled, if the corresponding input pin detects a valid trigger edge, the controller will lock the motor and stop responding to the stepping command, and the user can read the controller status to see which input pin triggered the emergency stop. Only when the user clears the corresponding status bit does the controller continue to respond

to new step commands.

### 5.8.1 External emergency stop enable

|                  |                         |
|------------------|-------------------------|
| Object name      | External emergency stop |
| Instruct address | 0x6013                  |
| Object type      | U8,rw                   |
| Range            | Bit                     |
| Storage type     | ROM                     |
| Default value    | 0                       |

This is represented by 1bit that each external emergency stop enable. 0 indicates the prohibition, and 1 indicates enabling. Its definition is as follows:

bit0: External emergency stop 1 enable settings

bit1: External emergency stop 2 enable settings

Set to 0 to turn off the two limit enables, set to 1, turn on the limit 1, turn off the limit 2, set to 2, turn off the limit 1, turn on the limit 2, set to 3, and turn on 1/2 of the two limits

### 5.8.2 The trigger mode of external emergency stop

|                  |                                             |
|------------------|---------------------------------------------|
| Object name      | The trigger mode of external emergency stop |
| Instruct address | 0x6014                                      |
| Object type      | U8,rw                                       |
| Range            | Bit                                         |
| Storage type     | ROM                                         |
| Default value    | 0                                           |

Trigger mode of each external emergency stop is represented by 1bit. 0 indicates falling edge trigger, and 1 indicates rising edge trigger. Its definition is as follows:

bit0: The trigger mode of external emergency stop 1

bit1: The trigger mode of external emergency stop 2

The same goes for setup and use

### 5.8.3 Sensor type

|                  |             |
|------------------|-------------|
| Object name      | Sensor type |
| Instruct address | 0x6015      |
| Object type      | U8,rw       |
| Range            | 0-1         |
| Storage type     | ROM         |
| Default value    | 0           |

You can modify the initial level value of limit 2 under different trigger modes, the default value is 0, the initial high level of the falling edge, and the initial low level of the rising edge

Set to 1, the falling edge is initially low, and the rising edge is initially high.

Its definition is as follows:

0: when the trigger mode is configured as the rising edge, the controller is configured as the internal pull-down resistance, When configured as a falling edge, the controller is configured with an internal pull-up resistor; typically used for an NPN type of sensor;

1: When the trigger mode is configured as the rising edge, the controller is configured as the internal pull-up resistance, when the trigger mode is configured as the falling edge, the controller is configured with the internal pull-down resistance, typically used for an PNP type of sensor;

#### 5.8.4 Debouncing delay

The trigger delay of external emergency stop can be modified by 0x6042 object. The controller delays the setting time after the detected edge signal, and then detects whether its level state is correct or not, then triggers the motor to stop urgently, otherwise the motor will continue to rotate.

|                  |                                     |
|------------------|-------------------------------------|
| Object name      | EXT1/EXT2/EXT3 stabilize delay (ms) |
| Instruct address | 0x6042                              |
| Object type      | U8,rw                               |
| Range            | 0~200                               |
| Storage type     | ROM                                 |
| Default value    | 30                                  |

The debouncing delay parameter needs to be stabilized in MS, and it can still meet the requirements of limit level detection, which can be analogous to the debounce delay application of keyboard keys.

### 5.9 General IO port

The PMC006B6 controller provides 1 output (GPO8) port, 2 external emergency stop input (EXT1/EXT2) ports

#### 5.9.1 IO port direction

|                  |                   |
|------------------|-------------------|
| Object name      | IO port direction |
| Instruct address | 0x602e            |
| Object type      | U16,rw            |
| Range            | 0, 1              |
| Storage type     | ROM               |
| Default value    | 0                 |

The direction of each IO port is represented by 1bit. 0 represents input, and 1 represents output. The meaning of each bit is as follow:

Bit0: GPIO1

Bit1: GPIO2

Bit2: GPIO3

Bit3: GPIO4

Bit4: GPIO5

Bit5: GPIO6  
 Bit6: GPIO7  
 Bit7: GPIO\_EXT1  
 Bit8: GPIO\_EXT2  
 Bit9: GPIO\_ENC1  
 Bit10: GPIO\_ENC2  
 Bit11: GPIO8  
 Bit12: FSET  
 Bit13: GPIO9

Among them, the direction of the emergency stop input port and the encoder input port is fixed as the input port and cannot be configured.

## 2、IO port configuration

|                  |                       |
|------------------|-----------------------|
| Object name      | IO port configuration |
| Instruct address | 0x602f..30            |
| Object type      | U32,rw                |
| Range            | 0-0x3fffff            |
| Storage type     | ROM                   |
| Default value    | 0                     |

Each port is configured by 2 bits. If the IO port is configured as a input port, the meaning of the value is as follows:

0: FLOATING  
 1: IPU  
 2: IPD  
 3: AIN

If the IO port is configured as a output port, the meaning of the value is as follows:

0: OD  
 1: PP

The definition of the IO port configuration is defined as follows:

Bit1-0: GPIO1  
 Bit3-2: GPIO2  
 Bit5-4: GPIO3  
 Bit7-6: GPIO4  
 Bit9-8: GPIO5  
 Bit11-10: GPIO6  
 Bit13-12: GPIO7  
 Bit15-14: GPIO\_EXT1  
 Bit17-16: GPIO\_EXT2  
 Bit19-18: GPIO\_ENC1  
 Bit21-20: GPIO\_ENC2  
 Bit23-22: GPIO8  
 Bit25-24: FSET  
 Bit27-26: GPIO9

### 5.9.2 General IO port value

|                  |                       |
|------------------|-----------------------|
| Object name      | General IO port value |
| Instruct address | 0x6031                |
| Object type      | U16,rw                |
| Range            | bit                   |
| Storage type     | RAM                   |
| Default value    | 0                     |

The value of each IO port is represented by 1bit, 0 indicates a high level, 1 indicates a low level, and writing value to the port is not valid for the input port. The meaning of each bit is as follows:

Bit0: GPIO1,  
 Bit1: GPIO2,  
 Bit2: GPIO3,  
 Bit3: GPIO4,  
 Bit4: GPIO5,  
 Bit5: GPIO6,  
 Bit6: GPIO7,  
 Bit7: GPIO\_EXT1,  
 Bit8: GPIO\_EXT2,  
 Bit9: GPIO\_ENC1,  
 Bit10 :GPIO\_ENC2,  
 Bit11: GPIO8,  
 Bit12: FSET,  
 Bit13: GPIO9

## 5.10 Closed-loop control

PMC006B6 supports 200-4000CPR incremental photoelectric encoder and uses PID to realize closed loop control. The following is a detailed description of the closed-loop parameters.

### 5.10.1 Encoder resolution

|                  |                                                                                                                     |
|------------------|---------------------------------------------------------------------------------------------------------------------|
| Object name      | Encoder resolution                                                                                                  |
| Instruct address | 0x6054                                                                                                              |
| Object type      | U16,rw                                                                                                              |
| Range            | Incremental encoder closed loop:<br>200,400,500,600,800,1000,1200,1600,2000,4000<br>Absolute encoder closed loop:14 |
| Storage type     | ROM                                                                                                                 |
| Default value    | 4000,14                                                                                                             |

Note: After changing the encoder resolution, the power of controller must be re-energize.

PPR: Encoder Accuracy/Number of Lines/Resolution

CPR: Encoder count

$CPR = PPR * 4$       CPR is the number of steps per lap.

**5.10.2 KP parameter**

|                  |              |
|------------------|--------------|
| Object name      | KP parameter |
| Instruct address | 0x6057       |
| Object type      | U8,rw        |
| Range            | 1-255        |
| Storage type     | ROM          |
| Default value    | 32           |

This parameter affects the transient response characteristic of the system.

**5.10.3 KI parameter**

|                  |              |
|------------------|--------------|
| Object name      | KI parameter |
| Instruct address | 0x6058       |
| Object type      | U8,rw        |
| Range            | 1-255        |
| Storage type     | ROM          |
| Default value    | 3            |

This parameter affects the cumulative error characteristics of the system.

**5.10.4 KD parameter**

|                  |              |
|------------------|--------------|
| Object name      | KD parameter |
| Instruct address | 0x6059       |
| Object type      | U8,rw        |
| Range            | 1-255        |
| Storage type     | ROM          |
| Default value    | 16           |

This parameter affects the transient response characteristic of the system.

**5.10.5 Pre-filtering parameter**

|                  |                         |
|------------------|-------------------------|
| Object name      | Pre-filtering parameter |
| Instruct address | 0x605a                  |
| Object type      | U8,rw                   |
| Range            | 1-128                   |
| Storage type     | ROM                     |
| Default value    | 40                      |

This parameter affects the speed characteristics of the system. When speed or microstepping is high, it is recommended to use larger parameter values.

**5.10.6 Post-filtering parameter**

|                  |                          |
|------------------|--------------------------|
| Object name      | Post-filtering parameter |
| Instruct address | 0x605b                   |
| Object type      | U32,rw                   |
| Range            | 1-65535                  |

|               |      |
|---------------|------|
| Storage type  | ROM  |
| Default value | 1330 |

This parameter is reserved for the time being.

#### 5.10.7 Stall length parameter

|                  |                        |
|------------------|------------------------|
| Object name      | Stall length parameter |
| Instruct address | 0x605c                 |
| Object type      | U16,rw                 |
| Range            | 1-255                  |
| Storage type     | ROM                    |
| Default value    | 7                      |

The larger the threshold value for judging the stalled rotor, the less sensitive it is.

#### 5.10.8 Torque ring enable(High-speed torque mode switch)

|                  |                    |
|------------------|--------------------|
| Object name      | Torque ring enable |
| Instruct address | 0x605d             |
| Object type      | U8,rw              |
| Range            | 0-1                |
| Storage type     | ROM                |
| Default value    | 0                  |

Toggle the switch in high-speed torque mode, write 1 into high-speed torque mode, and write 0 into normal mode.

#### 5.10.9 Autosave when power is off enable

|                  |                                   |
|------------------|-----------------------------------|
| Object name      | Autosave when power is off enable |
| Instruct address | 0x605e                            |
| Object type      | U8,rw                             |
| Range            | 0-1                               |
| Storage type     | ROM                               |
| Default value    | 0                                 |

The closed-loop takes effect, and the controller automatically detects the power-off of the system after it is enabled, and writes the current motor position into the EEPROM. At the same time, for singleturn and incremental encoder motors, it is necessary to ensure that the motor does not rotate after the power failure, which can be used with the solenoid valve. If the motor rotates in the event of a power failure, this saved value is meaningless.

### 5.11 PP motion mode

Set the working mode to 4 to PP mode(Profile Position Mode), which adopts trapezoidal acceleration and deceleration, and can set the start speed, stop speed, acceleration, deceleration, running speed and target position independently. In the process of PP mode operation, the host computer can be received to write a new set of parameters, and finally by writing the control

word to let the controller run smoothly from the previous motion parameters to the new parameters, or after the old parameters are completed, and then run with the new parameters.

#### 5.11.1 PP mode Acceleration

|                  |                                                 |
|------------------|-------------------------------------------------|
| Object name      | PP acceleration, pps/s                          |
| Unit             | Normal mode pps<br>High-speed mode 0.1 lines/ms |
| Instruct address | 0x6067..68                                      |
| Object type      | U32,rw                                          |
| Range            | Normal mode >150<br>High-speed mode >0          |
| Storage type     | ROM                                             |
| Default value    | Normal mode 32000<br>High-speed mode 50         |

#### 5.11.2 PP mode Deceleration

|                  |                                                 |
|------------------|-------------------------------------------------|
| Object name      | PP deceleration, pps/s                          |
| Unit             | Normal mode pps<br>High-speed mode 0.1 lines/ms |
| Instruct address | 0x6069..6a                                      |
| Object type      | U32,rw                                          |
| Range            | Normal mode >150<br>High-speed mode >0          |
| Storage type     | ROM                                             |
| Default value    | Normal mode 32000<br>High-speed mode 50         |

#### 5.11.3 PP mode Start speed

|                  |                                                 |
|------------------|-------------------------------------------------|
| Object name      | PP start speed, pps/s                           |
| Unit             | Normal mode pps<br>High-speed mode 0.1 lines/ms |
| Instruct address | 0x606b..6c                                      |
| Object type      | U32,rw                                          |
| Range            | Normal mode >150<br>High-speed mode >20         |
| Storage type     | ROM                                             |
| Default value    | 600                                             |

**5.11.4 PP mode Stop speed**

|                  |                                                 |
|------------------|-------------------------------------------------|
| Object name      | PP stop speed                                   |
| Unit             | Normal mode pps<br>High-speed mode 0.1 lines/ms |
| Instruct address | 0x606d..6e                                      |
| Object type      | U32,rw                                          |
| Range            | Normal mode >150<br>High-speed mode >20         |
| Storage type     | ROM                                             |
| Default value    | 600                                             |

**5.11.5 PP mode Control word**

|                  |                 |
|------------------|-----------------|
| Object name      | PP Control word |
| Instruct address | 0x6070          |
| Object type      | U16,rw          |
| Range            | ROM             |
| Storage type     | 0-0xFFFF        |
| Default value    | 0               |

The function description for Control word object 6070:

- Bit 4: Start task. Start the task when bit value switch from 0 to 1.
- Bit 5: The task triggered by Bit4 will be immediately executed if this bit is set 1. The task will be executed after last task completed if this bit is set 0.
- Bit 6: The target position (602e,4) is relative position when this bit is set 0, the target position is absolute position if this bit is set 1.
- Bit 8 (Halt): This bit is for PV motion mode, motor will be accelerated to target speed in preferred slope if this bit change from 1 to 0. Motor will be decelerated to zero if this bit change from 0 to 1.

**5.11.6 PP Status word**

|                  |                |
|------------------|----------------|
| Object name      | Pp status word |
| Instruct address | 0x6071         |
| Object type      | U16,rw         |
| Range            | ROM            |
| Storage type     | 0-0xFFFF       |
| Default value    | 0              |

The following bits in the status word object have special functions:

- bit0: When this bit is set, it will change the speed after reaching the first target position.

This means that the brakes are not applied until the first target is reached, because the motor should not stop in that position.

- bit1: When the final target has been reached, the bit will be set to "1".
- bit2 : This bit confirms the receipt of a valid new target point. This bit will be set and reset in sync with the bit "New Target Point" in the control word.

Exception: Start a new running task when one running task has not been completed and the next running task should be executed after the task is completed. In this case, the bit is reset only when the command has been accepted and the controller is ready to perform a new running task.

When one running task is enabled and another running task is scheduled, all other running tasks are ignored; In order to show this situation, this bit is set.

### 5.11.7 PP mode Running Speed

Subindex 0x03: running speed, the symbol represents the direction of rotation, the positive sign rotates positively, and the negative sign reverses

|                  |                                                 |
|------------------|-------------------------------------------------|
| Object name      | PP running speed                                |
| Unit             | Normal mode pps<br>High-speed mode 0.1 lines/ms |
| Instruct address | 0x6072..73                                      |
| Object type      | S32,rw                                          |
| Range            | ROM                                             |
| Storage type     | -300000- -150,150-300000                        |
| Default value    | 32000                                           |

### 5.11.8 PP mode Target Location


Subindex 0x04: PP mode Target Location

|                  |                                   |
|------------------|-----------------------------------|
| Object name      | Pp Target location                |
| Instruct address | 0x6074..75                        |
| Object type      | S32,rw                            |
| Range            | ROM                               |
| Storage type     | -2 <sup>31</sup> ~2 <sup>31</sup> |
| Default value    | 0                                 |

### 5.11.9 PP mode work timing


A new target position is set in the target position object (602e..75). Next, the bit 4 in the control word object (6070) is set for trigger the operation command. If the target location is valid, the controller will reply through the bit 12 in the object status word to locate the start of the

operation. When the location is reached, the bit 10 in the status word will immediately set to a "1".




Other running commands can be stored in the cache (see point in time 1 in the figure below), and bit 12 in the status word object (6071 sets the target point response) will be set to "0". During the motion to the target position, a second target position can be sent to the controller to prepare for it. At this point, you can reset all parameters, such as velocity, acceleration, deceleration, etc. (point in time 2). If the cache is idle again, the next point in time can enter the queue (point in time 3).

If the cache is full, the new target point will be ignored (point in time 4). If bit 5 in the control word object (6070 bit: "change the target point now") is set, the controller will not use cache when working, and the new running command will be executed directly (point in time 5).





The conversion process of the second target position:

The following figure shows the conversion process of the second target position when moving to the first target position. In this figure, the bit 5 of the control word object (6070) is set to "1" and the new target value will be accepted immediately.



The method of moving to the target position:

If the bit 9 in the control word object (6070) is a "0", it will first fully travel to the current target position. In this example, the final speed of the first target position is equal to zero. If bit 9 is set to "1", the final speed will be maintained until the target position is reached, and then the newly set motion parameters will take effect.



## 5.12 PV Mode

The working mode is set to 5 into (Profile Velocity Mode) PP mode, which adopts ladder acceleration and deceleration, and shares the starting speed, stop speed, acceleration, deceleration and running speed parameters with PP mode.

When the value of bit 8 (Halt) of the control word changes from "1" to "0", the motor will accelerate to the target speed with a preset starting speed in slope. When the value of the bit changes from "0" to "1", the motor slows down and stops moving. In the process of motion, a new running speed can be sent out, and the controller will smooth over to the newly set speed.

## 5.13 Analog positioning

PMC006B6 has an analog signal input port, and the internal 12-bit ADC, can be configured into analog positioning mode through software. First configure the analog positioning related parameters, and finally turn on the analog positioning enable. The following quart describes the

analog related objects in detail.

### 5.13.1 Enable analog positioning

Enable analog positioning, 1 open, 0 closed

|                  |                                  |
|------------------|----------------------------------|
| Object name      | Enable analog positioning 1 open |
| Instruct address | 0x6077                           |
| Object type      | U8,rw                            |
| Range            | ROM                              |
| Storage type     | 0、1                              |
| Default value    | 0                                |

### 5.13.2 Analog initial AD code

Analog quantity start AD code, corresponding to the minimum value of the analog position

|                  |                               |
|------------------|-------------------------------|
| Object name      | Analog quantity start AD code |
| Instruct address | 0x6078                        |
| Object type      | U16,rw                        |
| Range            | ROM                           |
| Storage type     | 0-4096                        |
| Default value    | 0                             |

### 5.13.3 Analog adjustment interval

Analog adjustment interval, Unit ms

The controller checks the analog input value at this time, and if the difference between the AD input value and the last input value is greater than the threshold value, the position will be adjusted once.

|                  |                            |
|------------------|----------------------------|
| Object name      | Analog adjustment interval |
| Instruct address | 0x6079                     |
| Object type      | U16,rw                     |
| Range            | ROM                        |
| Storage type     | 0-65535                    |
| Default value    | 100                        |

### 5.13.4 Analog regulating trigger value

The analog quantity adjusts the trigger value, and when the difference between the acquired AD code and the last acquired AD code is converted to a position greater than this value, the controller will adjust the position once.

|             |                                 |
|-------------|---------------------------------|
| Object name | Analog regulating trigger value |
|-------------|---------------------------------|

|                  |         |
|------------------|---------|
| Instruct address | 0x607a  |
| Object type      | U16,rw  |
| Range            | ROM     |
| Storage type     | 0-65535 |
| Default value    | 30      |

### 5.13.5 Minimum value of analog position

Minimum value of analog position: Absolute position corresponding to the analog start AD code

|                  |                                  |
|------------------|----------------------------------|
| Object name      | Minimum value of analog position |
| Instruct address | 0x607b..7c                       |
| Object type      | S32,rw                           |
| Range            | ROM                              |
| Storage type     | $-2^{31} \sim 2^{31}$            |
| Default value    | 0                                |

### 5.13.6 Maximum value of analog position

The absolute position corresponding to the AD code of 4095

|                  |                                  |
|------------------|----------------------------------|
| Object name      | Maximum value of analog position |
| Instruct address | 0x607d..7e                       |
| Object type      | S32,rw                           |
| Range            | ROM                              |
| Storage type     | $-2^{31} \sim 2^{31}$            |
| Default value    | 64000                            |

### 5.13.7 Analogue input read

The default voltage input is 0-3.3V, and special versions can support 4-20mA or 0-24V analog input, 12-bit ADC.

|               |                |
|---------------|----------------|
| Object name   | Analogue input |
| SDO ID        | 0x609c         |
| Object type   | U16,rw         |
| Range         | 0~4095         |
| Storage type  | RAM            |
| Default value | 0              |

## 5.14 Synchronous position Motion mode

The synchronous positioning motion mode can first set the absolute position and speed of

the specified node to run, and then make multiple axes move at the same time through the synchronous start command.

#### 5.14.1 SP speed

|                  |                        |
|------------------|------------------------|
| Object name      | SP speed               |
| Instruct address | 0x6047..48             |
| Object type      | S32,rw                 |
| Range            | -2147483648-2147483647 |
| Storage type     | RAM                    |
| Default value    | 2                      |

#### 5.14.2 SP position

|                  |                        |
|------------------|------------------------|
| Object name      | SP position            |
| Instruct address | 0x6049..4a             |
| Object type      | S32,rw                 |
| Range            | -2147483648-2147483647 |
| Storage type     | RAM                    |
| Default value    | 0                      |

#### 5.14.3 SP commands

|                  |             |
|------------------|-------------|
| Object name      | SP commands |
| Instruct address | 0000        |
| Object type      | U16, rw     |
| Range            | 0, a,       |
| Storage type     | RAM         |
| Default value    | 0           |

a: Synchronous operation command, absolute displacement

For controllers that need to be synchronized, set to different station numbers, the same group (i.e., the same group ID), and set the motion mode to position mode. The synchronous operation is operated in the absolute positioning mode of position mode, and the speed and position are set to 6047, 6048/6049, 604a respectively. After setting the values for the controllers at different stations, the instructions are sent to the groups to perform the movement by broadcasting.

The broadcast instruction is fixed at 06h to write a single function code, the address is 0, the register number is 0, the fourth byte is the group ID value, the fifth byte is the motion mode, and the synchronous execution value is A

06H instruction (Write a single hold register)

|             |                  |                |
|-------------|------------------|----------------|
| 485 address | Register address | Register value |
| 0           | 0000             | 010a           |

00 06 00 00 01 0A 09 8C

09 8C is the crc check code, and there is no response packet after the command is sent.

## 5.15 Soft limit function

PMC006B3 supports soft limit control to limit motor operation. When the switch is enabled, you can set the upper and lower limit positions to take effect, and when it runs to the upper limit and greater than the upper limit, the motor will stop the current forward rotation action and stop immediately, and the forward rotation command cannot be executed, and it can only reverse the operation to the upper limit range. The same goes for the lower limit.

### 5.15.1 Soft limit enable

|                  |                   |
|------------------|-------------------|
| Object name      | Soft limit enable |
| Instruct address | 0x6061            |
| Object type      | U16,rw            |
| Range            | 0~3               |
| Storage type     | RAM               |
| Default value    | 0                 |

bit0 and bit1 control switches. bit1 is the lower limit and bit0 is the upper limit.

### 5.15.2 Upper limit position

|                  |                      |
|------------------|----------------------|
| Object name      | Upper limit position |
| Instruct address | 0x6062/6063          |
| Object type      | S32,rw               |
| Range            | 0-0xffffffff         |
| Storage type     | RAM                  |
| Default value    | 0                    |

The upper limit bit position, the hexadecimal number with signs, and the value greater than 0x7fffffff is negative.

### 5.15.3 Lower limit position

|                  |                      |
|------------------|----------------------|
| Object name      | Lower limit position |
| Instruct address | 0x6064/65            |
| Object type      | S32,rw               |
| Range            | 0-0xffffffff         |
| Storage type     | RAM                  |
| Default value    | 0                    |

The lower limit position, a signed hexadecimal number, a value greater than 0x7fffffff is a negative number.

## 5.16 Brake control

The PMC006B3 supports brake control, and the output duty cycle can be adjusted via software to prevent the brake from overheating when powered for a long time.

|                  |               |
|------------------|---------------|
| Object name      | Brake control |
| Instruct address | 0x6038        |
| Object type      | U8,rw         |
| Range            | 0-100         |
| Storage type     | RAM           |
| Default value    | 0             |

## 5.17 Power loss behavior

PMC006B3 can detect the power loss of the system and set the corresponding power loss behavior. The following is a detailed description of the power loss behavior settings related objects.

### 5.17.1 Power-down behavior control word

|                  |                                    |
|------------------|------------------------------------|
| Object name      | Power-down behavior control switch |
| Instruct address | 0x6082                             |
| Object type      | U16,rw                             |
| Range            | ROM                                |
| Storage type     | bit                                |
| Default value    | 0                                  |

Bit0: detects power loss and goes offline

Bit1: Brake engage

The switch is turned on when the corresponding value is 1 and turned off for 0.

### 5.17.2 Power-down off-line voltage

|                  |                                    |
|------------------|------------------------------------|
| Object name      | Offline threshold voltage, unit mv |
| Instruct address | 0x6083                             |
| Object type      | U16,rw                             |
| Range            | ROM                                |
| Storage type     | 0-65535                            |
| Default value    | 0                                  |

When the offline switch is turned on, the motor is offline when the power supply voltage is detected to be below this voltage.

### 5.17.3 Power-off brake threshold voltage

Power-off brake threshold voltage, unit: mv

|                  |                                   |
|------------------|-----------------------------------|
| Object name      | Power-off brake threshold voltage |
| Instruct address | 0x6084                            |
| Object type      | U16,rw                            |
| Range            | ROM                               |

|               |         |
|---------------|---------|
| Storage type  | 0-65535 |
| Default value | 0       |

When the power-off brake function is enabled, the brake is applied when the supply voltage drops below this threshold.

#### 5.17.4 Supply voltage reading

Power-off brake threshold voltage, unit: mv

|                  |                     |
|------------------|---------------------|
| Object name      | Supply voltage (mV) |
| Instruct address | 0x605f              |
| Object type      | U16,rw              |
| Range            | -                   |
| Storage type     | ROM                 |
| Default value    | -                   |

#### 5.18 Open and closed loop function switching

|               |                                         |
|---------------|-----------------------------------------|
| Object name   | Open and closed loop function switching |
| SDO ID        | 0x6036-37                               |
| Object type   | U32,rw                                  |
| Range         | 0-1                                     |
| Storage type  | ROM                                     |
| Default value | 0                                       |

Write the value to the register, and write a power-off save instruction before it takes effect, after taking effect, the encoder reading will be shielded, and the open-loop method is used to control the motor operation. It is often used in emergency situations. The closed-loop version works.

#### 5.19 Temperature threshold

|               |                       |
|---------------|-----------------------|
| Object name   | Temperature threshold |
| SDO ID        | 0x6035                |
| Object type   | U8,rw                 |
| Range         | 100-135               |
| Storage type  | ROM                   |
| Default value | 0x64                  |

When the detection value is higher than the set threshold, the motor state (6000h) will be set to overheat, and the motor enable (600b) will be set to 0 to protect the controller.

#### 5.20 Motor wiring configuration

|             |                            |
|-------------|----------------------------|
| Object name | Motor wiring configuration |
| SDO ID      | 0x6086                     |
| Object type | U8,rw                      |
| Range       | 0-3                        |

|               |     |
|---------------|-----|
| Storage type  | ROM |
| Default value | 3   |

Using the register for direction control, you can change the reading direction of the motor and encoder without changing the physical line sequence, where bit0 is the motor line sequence, bit1 is the encoder line sequence, the default is 03, and the version needs to be at least V388 or above.

## 5.21 Homing configuration

### 5.21.1 Homing speed

|                  |              |
|------------------|--------------|
| Object name      | Homing speed |
| Instruct address | 0x6098..99   |
| Object type      | U32, rw      |
| Storage type     | RAM          |
| Range            | 0-0xFFFFFFFF |
| Default value    | 0            |

### 5.21.2 Homing distance

|                  |                 |
|------------------|-----------------|
| Object name      | Homing distance |
| Instruct address | 0x609a..9b      |
| Object type      | U32, rw         |
| Storage type     | RAM             |
| Range            | 0-0xFFFFFFFF    |
| Default value    | 0               |

After setting the homing speed and homing distance, the motor will run forward until it triggers EXT2, and the current position will be recorded as zero. When homing at the limit, the motor first moves backward a quarter of the homing distance, then moves forward to find the zero point.

## 5.22 offline programming

The controller sets the corresponding parameters according to the process. From top to bottom, run sequentially. At the same time, according to the judgment conditions, jump to the program with the specified serial number and continue to run down in turn. Writing an offline program with instructions requires writing the overall number of instructions first, and then writing each instruction based on the pointer value, starting with clause 0, each writes a pointer first, and then writes the specific value and instruction.

Commands can be saved to select the corresponding directives and subset specific functions according to the instructions in the settings file 'PMC006BX.pusi'. If there is no delay in each instruction, the execution speed from top to bottom is counted in microseconds. So if the internal process doesn't write the wait condition correctly or compare the judgment condition. Then there may be cases where the process runs into other loops before it is finished. Generally, after sending the operation instruction, it will be followed by an instruction to wait for the completion of the step, or a command to wait for the time, so that the motor can run the set

number of steps. If there is no waiting instruction, the program will continue to execute. At this time, the motor is running, then subsequent commands will not take effect or replace the current running task.

#### 5.22.1 The total number of offline program instructions

|               |                                                  |
|---------------|--------------------------------------------------|
| Object name   | The total number of offline program instructions |
| SDO ID        | 0x603b                                           |
| Object type   | Record                                           |
| Storage type  | ROM                                              |
| Default value | 0                                                |

The total number of offline instructions that were read and written.

#### 5.22.2 Offline automatic operation enable

|               |                                    |
|---------------|------------------------------------|
| Object name   | Offline automatic operation enable |
| SDO ID        | 0x603c                             |
| Object type   | Record                             |
| Storage type  | ROM                                |
| Default value | 0                                  |

Write 1 to start the execution process

#### 5.22.3 Offline program pointers

|               |                          |
|---------------|--------------------------|
| Object name   | Offline program pointers |
| SDO ID        | 0x603d                   |
| Object type   | Record                   |
| Storage type  | ROM                      |
| Default value | 0                        |

Indicates the number of serial numbers that are currently being executed

#### 5.22.4 Set the content of the offline command

|               |                                        |
|---------------|----------------------------------------|
| Object name   | Set the content of the offline command |
| SDO ID        | 0x603e...f                             |
| Object type   | Record                                 |
| Storage type  | ROM                                    |
| Default value | 0                                      |

603e is the high value, which corresponds to the specific value set by the command.

603f is the low value, corresponding to the command options and functions, the options are in the high position, and the function is in the low position

#### 5.22.5 Save offline commands

|             |                       |
|-------------|-----------------------|
| Object name | Save offline commands |
| SDO ID      | 0x6040                |

|               |        |
|---------------|--------|
| Object type   | Record |
| Storage type  | ROM    |
| Default value | 0      |

Save the command and save it to the controller, and write 1 takes effect. It needs to be used with the power-off save command.

#### 5.22.6 Test run instructions

|               |                       |
|---------------|-----------------------|
| Object name   | Test run instructions |
| SDO ID        | 0x6041                |
| Object type   | Record                |
| Storage type  | ROM                   |
| Default value | 0                     |


Whether to run the command corresponding to the current pointer, write 1 to take effect. After execution, the serial number corresponding to the pointer is sent to perform the test. It is often used to test the function of the command, such as setting the current, speed, and verifying whether it is valid

Example of an offline command:

Set the format of the offline command: Take 01 10 60 3E 00 02 04 03 E8 07 77 1B 53 as an example: his data part is 03 E8 07 77. 03E8 is the parameter value of the offline command, which is 1000; 07 77 corresponds to option 7 of the w instruction, i.e., waiting for Nms in the waiting instruction; The full meaning is that the offline command corresponding to the current pointer is to wait for 1000 ms. The specific instructions need to be combined with the files that come with the test software.

## 6 Electrical Characteristics

| Parameter             | Condition           | Min  | Typical | Max | Unit |
|-----------------------|---------------------|------|---------|-----|------|
| Supply Power Voltage  | Normal 25°C         | 9    | 24      | 48  | V    |
| Operation Temperature | 24V DC              | -40  |         | 85  | °C   |
| IO maximum current    | source/sink current | 0    | 10      | 20  | mA   |
| Output current        | Normal 25°C         | 0.4  | 4       | 6   | A    |
| IO low Voltage        | 24V DC              | -0.5 |         | 1.0 | V    |
| IO High Voltage       | 24V DC              | 3.0  |         | 5.5 | V    |

**7 Dimensions (unit: mm)**

## 8 Appendix 1 instruction table

| Modbus address | Name                                             | Data Type | Attr. |
|----------------|--------------------------------------------------|-----------|-------|
| 2028           | Slave address                                    | UINT8     | RW    |
| 202a. . b      | Baud rate                                        | UINT32    | RW    |
| 6000           | Error state                                      | UINT8     | RW    |
| 6001           | Controller status                                | UINT8     | RW    |
| 6002           | Rotation direction                               | UINT8     | RW    |
| 6003. . 4      | Max speed                                        | INT32     | RW    |
| 6005. . 6      | Step command                                     | INT32     | RW    |
| 6007           | Operation mode                                   | UINT8     | RW    |
| 6008           | Start speed                                      | UINT16    | RW    |
| 6009           | Stop speed                                       | UINT16    | RW    |
| 600a           | Acceleration coefficient                         | UINT8     | RW    |
| 600b           | Deceleration coefficient                         | UINT8     | RW    |
| 600c           | Microstepping                                    | UINT16    | RW    |
| 600d           | Max phase current                                | UINT16    | RW    |
| 600e. . f      | Motor position                                   | INT32     | RW    |
| 6010           | Current attenuation                              | UINT8     | RW    |
| 6011           | Motor enable                                     | UINT8     | RW    |
| 6013           | External emergency stop enable                   | UINT8     | RW    |
| 6014           | Trigger mode of external emergency stop          | UINT8     | RW    |
| 6015           | Type of sensor                                   | UINT8     | RW    |
| 602e           | GPIO diriction                                   | UINT16    | RW    |
| 602f. . 30     | GPIO configuration                               | UINT32    | RW    |
| 6031           | GPIO value                                       | UINT16    | RW    |
| 603b           | The total number of offline program instructions | UINT16    | RW    |
| 603c           | Offline automatic operation enable               | UINT16    | RW    |
| 603d           | Offline program pointer                          | UINT16    | RW    |
| 603e...f       | Set the content of the offline command           | UINT16    | RW    |
| 6040           | Save offline commands                            | UINT16    | RW    |

|           |                                               |        |    |
|-----------|-----------------------------------------------|--------|----|
| 6041      | Test run instructions                         | UINT16 | RW |
| 6042      | Jitter delay of external emergency stop       | UINT32 | RW |
| 6043      | Locked-Rotor configuration                    | UINT8  | RW |
| 6044. . 5 | Absolute position step                        | INT32  | RW |
| 6053      | Termination step                              | UINT8  | RW |
| 6054      | encoder CPR                                   | UINT16 | RW |
| 6055. . 6 | Position saving value power-down              | INT32  | RO |
| 6057      | Closed-loop parameter KP                      | UINT8  | RW |
| 6058      | Closed-loop parameter KI                      | UINT8  | RW |
| 6059      | Closed-loop parameter KD                      | UINT8  | RW |
| 605a      | Closed-loop Pre-filter parameter              | INT8   | RW |
| 605b      | Closed-loop post-filter parameter             | INT16  | RW |
| 605c      | Closed-loop stall length                      | INT16  | RW |
| 605d      | Enable closed-loop torque loop                | UINT8  | RW |
| 605e      | Enable saving automatically when power is off | UINT8  | RW |
| 605f      | Analogue input                                | UINT16 | RW |
| 6061      | Step notification status                      | UINT8  | RW |
| 6062. . 3 | Step notification position 1                  | INT32  | RW |
| 6064. . 5 | Step notification position 2                  | INT32  | RW |
| 6067. . 8 | PP/PV mode Accelerated speed                  | UINT32 | RW |
| 6069. . a | PP/PV mode Dccelerated speed                  | UINT32 | RW |
| 606b. . c | PP/PV mode Initial speed                      | UINT32 | RW |
| 606d. . e | PP/PV mode Stop speed                         | UINT32 | RW |
| 6070      | PP/PV mode control word                       | UINT16 | RW |
| 6071      | PP/PV mode status                             | UINT16 | RW |

|              |                                        |        |    |
|--------------|----------------------------------------|--------|----|
|              | word                                   |        |    |
| 6072. . 3    | PP/PV mode running speed               | INT32  | RW |
| 6074. . 5    | PP/PV mode target location             | INT32  | RW |
| 6077         | Enable analog positioning              | UINT8  | RW |
| 6078         | Analog initial AD code                 | UINT16 | RW |
| 6079         | Analog adjustment interval time        | UINT16 | RW |
| 607a         | Analog regulating trigger value        | UINT16 | RW |
| 607b. . c    | Minimum value of analog position       | INT32  | RW |
| 607d. . e    | Maximum value of analog position       | INT32  | RW |
| 607f. . 80   | real-time speed                        | INT32  | RW |
| 6082         | Power-down behavior control word       | UINT16 | RW |
| 6083         | Power off motor enabling threshold     | UINT16 | RW |
| 6084         | Brake lock threshold                   | UINT16 | RW |
| 6086         | Motor line sequence configuration      | UINT16 | RW |
| 6089. . 608a | Encoder position                       | INT32  | RW |
| 6098. . 6099 | Homing speed                           | INT32  | RW |
| 609a. . 609b | Homing distance                        | INT32  | RW |
| 609c         | Read the analog value of the interface | UINT16 | RW |

## 9 Appendix 2 Communications Example

### 9.1 Modbus/RTU supported function codes

PMC006B6xP currently supports the following function codes:

- 1、0x03: read holding register;
- 2、0x06: write single register;
- 3、0x10: write multiple registers;

### 9.2 Master Station communication parameter setting:

- 1) Baud rate: Same as slave station ;
- 2) Data bit: 8;
- 3) Stop bit: 1;
- 4) Parity bit: None;

### 9.3 Modbus master station message write operation

1) Function code 03:

Read the data in user registers 600C and 600D, and the message is as follows:

Read packet: 01 (site) 03 (instruction) 60 0C (register bit) 00 02 (number of reads) 1A 08 (CRC code)

Feedback packet: 01 (site) 03 (command) 04 (number of returned data) 00 00 04 0A (data) 78 F4 (CRC check dignified)

2) Function code 06:

The data value written to user register 600c is 32(0x20): and the packet is as follows:

Write message: 01 (site) 06 (instruction) 60 0C (register bit) 00 20 (write a single data) 56 11 (CRC code)

Feedback message: 01 06 60 0C 00 20 56 11

3) Function code 10:

For example, data 2 (0x0002), 588 (0x292), 0 (0x0000), and 3 (0x0003) are to be written to 600C, 600D, 600E, and 600D, respectively, and the packets are as follows:

Write packets: 01 (site) 10 (instruction) 60 0c (start register bit) 00 04 (write 4 data) 08 (8 bytes) 00 02 02 92 00 00 00 03 (write data) 9f f5 (CRC checksum)

Feedback packet: 01 10 60 0c 00 04 1f c9

### 9.4 Modbus/RTU control examples

#### 9.4.1 Relative position control

| Controller address | Function code | Register address | Data(0x) | Description                                       | Remarks            |
|--------------------|---------------|------------------|----------|---------------------------------------------------|--------------------|
| 01                 | 06            | 600c             | 0020     | Set microstep to 32                               |                    |
| 01                 | 06            | 600d             | 03e8     | Set max phrase current to 1000                    |                    |
| 01                 | 06            | 6003             | 0000     | Set the high 16 bits of speed to 0                |                    |
| 01                 | 06            | 6004             | 7d00     | Set the low 16 bits of speed to 32000(300RPM)     |                    |
| 01                 | 06            | 6002             | 0000     | Set the rotation direction to be positive         |                    |
| 01                 | 06            | 6005             | 0000     | Set the high 16 bits of relative position to 0    |                    |
| 01                 | 06            | 6006             | 7d00     | Set the low 16 bits of relative position to 32000 |                    |
| 01                 | 03            | 6001             | 0000     | Read controller                                   | The value of bit3: |

|  |  |  |  |                                  |                        |
|--|--|--|--|----------------------------------|------------------------|
|  |  |  |  | statu,bit3 is busy<br>status bit | 1:busy<br>0:motor stop |
|--|--|--|--|----------------------------------|------------------------|

#### 9.4.2 Absolute position control

| Controller address | Function code | Register address | Data(0x) | Description                                     | Remarks                                      |
|--------------------|---------------|------------------|----------|-------------------------------------------------|----------------------------------------------|
| 01                 | 06            | 600c             | 0020     | Set microstep to 32                             |                                              |
| 01                 | 06            | 600d             | 03e8     | Set max phrase current to 1000                  |                                              |
| 01                 | 06            | 6003             | 0000     | Set the high 16 bits of speed to 0              |                                              |
| 01                 | 06            | 6004             | 7d00     | Set the low 16 bits of speed to 32000(300RPM)   |                                              |
| 01                 | 06            | 6044             | 0000     | Set the rotation direction to be positive       |                                              |
| 01                 | 06            | 6045             | 7d00     | Set the high 16 bits of relative position to 0  |                                              |
| 01                 | 03            | 6001             | 0000     | Read controller status, busy status bit of bit3 | The value of bit3:<br>1:busy<br>0:motor stop |

#### 9.4.3 Speed mode control

| Controller address | Function code | Register address | Data(0x) | Description                                   | Remarks                                      |
|--------------------|---------------|------------------|----------|-----------------------------------------------|----------------------------------------------|
| 01                 | 06            | 600c             | 0020     | Set microstep to 32                           |                                              |
| 01                 | 06            | 600d             | 03e8     | Set max phrase current to 1000                |                                              |
| 01                 | 06            | 6007             | 0001     | Set work mode to speed mode                   |                                              |
| 01                 | 06            | 6003             | 0000     | Set the high 16 bits of speed to 0            |                                              |
| 01                 | 06            | 6004             | 7d00     | Set the low 16 bits of speed to 32000(300RPM) |                                              |
| 01                 | 03            | 6001             | 0000     | Read controller statu,bit3 is busy status bit | The value of bit3:<br>1:busy<br>0:motor stop |

**9.4.4 Commonly used fixed parameter settings**

| Controller address | Function code | Register address | Data(0x) | Description                             | Remarks                           |
|--------------------|---------------|------------------|----------|-----------------------------------------|-----------------------------------|
| 01                 | 06            | 600c             | 0020     | Set microstep to 32                     |                                   |
| 01                 | 06            | 600d             | 03e8     | Set max phrase current to 1000          |                                   |
| 01                 | 06            | 6008             | 0258     | Set start speed to 600                  |                                   |
| 01                 | 06            | 6009             | 0258     | Set stop speed to 600                   |                                   |
| 01                 | 06            | 600a             | 0008     | Set Acceleration coefficient to 8       |                                   |
| 01                 | 06            | 600b             | 0008     | Set deceleration coefficient to 8       |                                   |
| 01                 | 06            | 6013             | 0003     | Enable external stop                    | Both of EXT1/EXT2 enabled         |
| 01                 | 06            | 6014             | 0000     | Trigger mode of external emergency stop | Both of EXT1/EXT2 are drop edge . |
| 01                 | 06            | 200f             | 0002     | Power-down saves all parameters         |                                   |

**10 Appendix 3 CRC code**

Cyclic redundancy check CRC area is 2 bytes, containing a 16-bit binary data. the CRC value is calculated by the sending device, and the calculated value is attached to the information. when the receiving device receives the information, the CRC value is recalculated, and the calculated value is compared with the actual value received in the CRC area. if the two are not the same, an error is generated.

CRC start by setting all the 16 bits of the register as "1", and then putting the data of the adjacent 2 8-bit bytes into the current register, only the 8-bit data of each character is used as the starting bit CRC, the generation, and the stop bit and parity bit are not added to the CRC.

The result of every 8 bits of data is shifted one bit to the right (in the LSB direction) during the generation of CRC, and the MSB, detection is filled with "0". If the LSB is "1", it is different from the preset fixed value, and if the LSB is "0", it is not different or operated.

Repeat the above procedure until the shift is 8 times. After the 8th shift is completed, the next 8-bit data is different from the current value of the register, and after all the information is processed, the final value in the register is CRC value.

CRC generation process:

1. Set the 16-bit CRC register FFFFH.
2. A first 8-bit data performs an XOR operation with a CRC register 8 bits lower, putting the result into the CRC register.
3. Move one bit CRC register to the right, MSB fill zero, check LSB..
4. (if LSB is 1): CRC register performs an XOR operation with the A001H.  
(If LSB is 0): Repeat 3 and move one bit to the right.

5. Repeat 3 and 4 until 8 shifts are completed and 8 bytes are processed.
6. Repeat steps 2 to 5 to process the next 8-bit data until all bytes are processed.
7. the final value of the CRC register is the CRC value.
8. high 8 bits and low 8 bits should be placed separately when putting the CRC value into the information. Add CRC values to the information, send the 16 bit CRC value in the message, first send low 8 bit, then send high 8 bit.

## 11 Appendix 3 Modbus/RTU 16bits CRC check example

```

1  // CRC High byte value table
2  static const uint8_t s_CRCHi[] = {
3      0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41, 0x01, 0xC0,
4      0x80, 0x41, 0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41,
5      0x00, 0xC1, 0x81, 0x40, 0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0,
6      0x80, 0x41, 0x01, 0xC0, 0x80, 0x41, 0x00, 0xC1, 0x81, 0x40,
7      0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41, 0x00, 0xC1,
8      0x81, 0x40, 0x01, 0xC0, 0x80, 0x41, 0x01, 0xC0, 0x80, 0x41,
9      0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41, 0x00, 0xC1,
10     0x81, 0x40, 0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41,
11     0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41, 0x01, 0xC0,
12     0x80, 0x41, 0x00, 0xC1, 0x81, 0x40, 0x00, 0xC1, 0x81, 0x40,
13     0x01, 0xC0, 0x80, 0x41, 0x01, 0xC0, 0x80, 0x41, 0x00, 0xC1,
14     0x81, 0x40, 0x01, 0xC0, 0x80, 0x41, 0x00, 0xC1, 0x81, 0x40,
15     0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41, 0x01, 0xC0,
16     0x80, 0x41, 0x00, 0xC1, 0x81, 0x40, 0x00, 0xC1, 0x81, 0x40,
17     0x01, 0xC0, 0x80, 0x41, 0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0,
18     0x80, 0x41, 0x01, 0xC0, 0x80, 0x41, 0x00, 0xC1, 0x81, 0x40,
19     0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41, 0x01, 0xC0,
20     0x80, 0x41, 0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41,
21     0x00, 0xC1, 0x81, 0x40, 0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0,
22     0x80, 0x41, 0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41,
23     0x01, 0xC0, 0x80, 0x41, 0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0,
24     0x80, 0x41, 0x00, 0xC1, 0x81, 0x40, 0x00, 0xC1, 0x81, 0x40,
25     0x01, 0xC0, 0x80, 0x41, 0x01, 0xC0, 0x80, 0x41, 0x00, 0xC1,
26     0x81, 0x40, 0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41,
27     0x00, 0xC1, 0x81, 0x40, 0x01, 0xC0, 0x80, 0x41, 0x01, 0xC0,
28     0x80, 0x41, 0x00, 0xC1, 0x81, 0x40
29 } ;
30 // CRC Low byte value table
31 const uint8_t s_CRCLo[] = {
32     0x00, 0xC0, 0xC1, 0x01, 0xC3, 0x03, 0x02, 0xC2, 0xC6, 0x06,
33     0x07, 0xC7, 0x05, 0xC5, 0xC4, 0x04, 0xCC, 0x0C, 0x0D, 0xCD,
34     0x0F, 0xCF, 0xCE, 0x0E, 0x0A, 0xCA, 0xCB, 0x0B, 0xC9, 0x09,
35     0x08, 0xC8, 0xD8, 0x18, 0x19, 0xD9, 0x1B, 0xDB, 0xDA, 0x1A,
    
```

```

36     0x1E, 0xDE, 0xDF, 0x1F, 0xDD, 0x1D, 0x1C, 0xDC, 0x14, 0xD4,
37     0xD5, 0x15, 0xD7, 0x17, 0x16, 0xD6, 0xD2, 0x12, 0x13, 0xD3,
38     0x11, 0xD1, 0xD0, 0x10, 0xF0, 0x30, 0x31, 0xF1, 0x33, 0xF3,
39     0xF2, 0x32, 0x36, 0xF6, 0xF7, 0x37, 0xF5, 0x35, 0x34, 0xF4,
40     0x3C, 0xFC, 0xFD, 0x3D, 0xFF, 0x3F, 0x3E, 0xFE, 0xFA, 0x3A,
41     0x3B, 0xFB, 0x39, 0xF9, 0xF8, 0x38, 0x28, 0xE8, 0xE9, 0x29,
42     0xEB, 0x2B, 0x2A, 0xEA, 0xEE, 0x2E, 0x2F, 0xEF, 0x2D, 0xED,
43     0xEC, 0x2C, 0xE4, 0x24, 0x25, 0xE5, 0x27, 0xE7, 0xE6, 0x26,
44     0x22, 0xE2, 0xE3, 0x23, 0xE1, 0x21, 0x20, 0xE0, 0xA0, 0x60,
45     0x61, 0xA1, 0x63, 0xA3, 0xA2, 0x62, 0x66, 0xA6, 0xA7, 0x67,
46     0xA5, 0x65, 0x64, 0xA4, 0x6C, 0xAC, 0xAD, 0x6D, 0xAF, 0x6F,
47     0x6E, 0xAE, 0xAA, 0x6A, 0x6B, 0xAB, 0x69, 0xA9, 0xA8, 0x68,
48     0x78, 0xB8, 0xB9, 0x79, 0xBB, 0x7B, 0x7A, 0xBA, 0xBE, 0x7E,
49     0x7F, 0xBF, 0x7D, 0xBD, 0xBC, 0x7C, 0xB4, 0x74, 0x75, 0xB5,
50     0x77, 0xB7, 0xB6, 0x76, 0x72, 0xB2, 0xB3, 0x73, 0xB1, 0x71,
51     0x70, 0xB0, 0x50, 0x90, 0x91, 0x51, 0x93, 0x53, 0x52, 0x92,
52     0x96, 0x56, 0x57, 0x97, 0x55, 0x95, 0x94, 0x54, 0x9C, 0x5C,
53     0x5D, 0x9D, 0x5F, 0x9F, 0x9E, 0x5E, 0x5A, 0x9A, 0x9B, 0x5B,
54     0x99, 0x59, 0x58, 0x98, 0x88, 0x48, 0x49, 0x89, 0x4B, 0x8B,
55     0x8A, 0x4A, 0x4E, 0x8E, 0x8F, 0x4F, 0x8D, 0x4D, 0x4C, 0x8C,
56     0x44, 0x84, 0x85, 0x45, 0x87, 0x47, 0x46, 0x86, 0x82, 0x42,
57     0x43, 0x83, 0x41, 0x81, 0x80, 0x40
58 };
59 /*
60 *****
61 *****
62 *   function name: CRC16_Modbus
63 *   description: CRC  _Modbus
64 *   Parameters: _pBuf : Data for validation
65 *               _usLen :Data length
66 *   Return value: 16bit integer value。   For Modbus, this result, high bytes are transmitted first,
67 *               low bytes are transmitted later..
68 *****
69 *****
70 */
71 uint16_t CRC16_Modbus(uint8_t * _pBuf, uint16_t _usLen)
72 {
73     uint8_t ucCRCHi = 0xFF; /* High CRC byte initial */
74     uint8_t ucCRCLo = 0xFF; /* Low CRC byte initial */
75     uint16_t usIndex; /* CRCindex in the loop */
76
77     while (_usLen--)
78     {
79         usIndex = ucCRCHi ^ *_pBuf++; /* calculate CRC */
80     }
81 }

```

```
77     ucCRCHi = ucCRCLo ^ s_CRCHi[usIndex];
78     ucCRCLo = s_CRCLo[usIndex];
79     }
80     return ((uint16_t)ucCRCHi << 8 | ucCRCLo);
81 }
```

Here's the calling method 1:

```
1     typedef struct
2     {
3         uint8_t RxBuf[H_RX_BUF_SIZE];
4         uint8_t RxCount;
5         uint8_t RxStatus;
6         uint8_t RxNewFlag;
7
8         uint8_t RspCode;
9
10        uint8_t TxBuf[H_TX_BUF_SIZE];
11        uint8_t TxCount;
12
13        uint16_t Reg01H;        /* Save the register header address sent by the host */
14        uint16_t Reg02H;
15        uint16_t Reg03H;
16        uint16_t Reg04H;
17
18        uint8_t RegNum;        /* register number */
19
20        uint8_t fAck01H;        /* Response command flag 0 indicates execution failure 1
    indicates execution success */
21        uint8_t fAck02H;
22        uint8_t fAck03H;
23        uint8_t fAck04H;
24        uint8_t fAck05H;
25        uint8_t fAck06H;
26        uint8_t fAck10H;
27
28    }MODH_T;
29    MODH_T g_tModH;
30    uint16_t crc;
31
32    g_tModH.TxBuf[0] = 0x31;
33    g_tModH.TxBuf[1] = 0x32;
34    g_tModH.TxCount = 2;
35    crc = CRC16_Modbus(g_tModH.TxBuf, g_tModH.TxCount);
```

Here's the calling method 2:

```

1  uint8_t _Data[10]; = { 0x31, 0x32 };
2  uint8_t usLen = 2;
3  crc = CRC16_Modbus(_Data, usLen);
4
```

## 12 Appendix 2 Error code table

| MODBUS ERROR CODE |                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code              | name                    | description                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 01                | Illegal function        | For the server (or slave), the function code received in the inquiry is an unallowed operation. This may be because the function code is only applicable to new devices and is not achievable in the selected unit. At the same time, it is also pointed out that the server (or slave) handles this kind of request in an error state, for example: because it is unconfigured, and it is required to return the register value.                   |
| 02                | Illegal data address    | For the server (or slave), the data address received in the inquiry is an unallowable address. In particular, the combination of reference number and transmission length is invalid. For a controller with 100 registers, the request with offset 96 and length 4 will succeed, and the request with offset 96 and length 5 will generate exception code 02.                                                                                       |
| 03                | Illegal data value      | For the server (or slave), the value included in the query is not allowed. This value indicates a failure in the remaining structure of the combined request, for example: the implied length is incorrect. It does not mean that because the MODBUS protocol does not know the significance of any special value of any special register, the data item submitted for storage in the register has a value that is not expected by the application. |
| 04                | Slave equipment failure | When the server (or slave) is trying to perform the requested operation, an unrecoverable error occurs.                                                                                                                                                                                                                                                                                                                                             |
| 05                | Ensure                  | Used with programming commands. The server (or slave) has accepted the request and is processing the request, but it takes a long time to perform these operations. Returning this response prevents a timeout error in the client (or master). The client (or master station) can continue to send the polling procedure completion message to determine whether the processing is completed.                                                      |
| 06                | Slave equipment busy    | Used with programming commands. The server (or slave) is processing long-duration program commands. When the Zhang server (or slave station) is idle, the user (or master station) should retransmit the message later.                                                                                                                                                                                                                             |

|    |                                         |                                                                                                                                                                                                                                                                                                                                        |
|----|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 08 | Storage parity error                    | Used with function codes 20 and 21 and reference type 6 to indicate that the extended file area cannot pass the consistency check. The server (or slave) managed to read the log file, but found a parity error in the memory. The client (or master) can resend the request, but can request service on the server (or slave) device. |
| 0A | Unavailable gateway path                | Used with a gateway to indicate that the gateway cannot allocate an internal communication path from input port to output port for processing requests. Usually means that the gateway is misconfigured or overloaded.                                                                                                                 |
| 0B | Gateway target device failed to respond | Used with the gateway to indicate that no response was obtained from the target device. Usually means that the device is not on the network.                                                                                                                                                                                           |

Examples of client requests and server exception responses:

| Request           |     | Response      |     |
|-------------------|-----|---------------|-----|
| domain name       | Hex | domain name   | Hex |
| Function code     | 01  | Function code | 81  |
| Start address(Hi) | 04  | Error code    | 02  |
| Start address(Lo) | A1  |               |     |
| Output number(Hi) | 00  |               |     |
| Output number(Lo) | 01  |               |     |

In this example, the client addresses the server device's request. Function code (01) is used to read the output status. It will request the output status of address 1245 (hex 04A1). It is worth noting that, as explained in the output field (0001) number, only one output is available. If there is no output address in the server device, the server will return an exception response with an exception code (02). This shows the illegal data address of the slave.

**Remarks:** The abnormal response message has two fields different from the normal response:

**Function code field:** In a normal response, the server uses the response function code field to respond to the originally requested function code. The most significant bit (MSB) of all function codes is 0 (their values are all lower than 80 hex). In the abnormal response, the server sets the MSB of the function code to 1. This makes the function code value in the abnormal response higher than the function code value in the normal response by 80 hexadecimal.

**Data field:** In a normal response, the server can return the data or statistics table in the data field (any message requested in the request). In the exception response, the server returns the exception code in the data field. This defines the server state that caused the exception.